

Biffi ICON3000

Intelligent, Multi-turn Electric Valve Actuator



This page is intentionally left blank.

Table of Contents

Section 1: Terminology

Terminology	5
-------------------	---

Section 2: Electric Technical Data

Electric Technical Data	5
-------------------------------	---

Section 3: Electric Data

Three-Phase AC	6
Single-Phase AC	50
Direct Current	53

This page is intentionally left blank.

Terminology

Nominal Torque

- Seating torque output of the actuator at full load.
- Output Torque with torque switch setting of 100%.

Minimum Torque

- Minimum output torque switch setting up to 40% of Nominal Torque.
- Adjustable in OPEN and in CLOSED direction.

Stall Torque

- Maximum torque/thrust during the initial start of output when the motor is energized and the output drive is locked.
- Stall Torque will be up to 2 times the Nominal Torque depending on speed and voltage.

Torque By-Pass

- Torque intervention bypass time function allows the actuator to output its stall torque at the beginning of the stroke.
- This allows a stall torque to be developed in order to operate sticking valves.
- By-Pass period time configurable from 0 to 20% or 100 to 80% of the stroke.

Modulating Torque

- Maximum torque for modulating duty.
- For 100% nominal voltage, +40 °C ambient temperature and at modulating torque load.

Jammed valve

- Time on which the actuator can supply the Stall Torque during the Torque By-Pass period.

Electric Technical Data

Motor Voltage Operation

- Voltage at which the actuator must be able to supply its nominal torque and within the power supply.
- Tolerances $\pm 10\%$
Applies on Nominal torque performance only; duty cycle, speed and current draw is not guaranteed.

Motor Frequency Operation

- Frequency at which the actuator must be able to supply its nominal torque and within the frequency.
- Tolerances $\pm 5\%$
Applies on Nominal torque performance only; duty cycle, speed and current draw is not guaranteed.

Motor Output Power (KW)

- Mechanical power output at motor shaft at run torque of multi-turn actuator.
- (Approximately 40% of actuator rated torque). According to IEC 60034-1.

Nominal current (In)

- Current at run torque at approximately 40% of nominal torque (minimum torque).

Rated current (Is)

- Motor current at approximately 100% of actuator nominal torque.

Locked current (Icc)

- Current at maximum torque (locked rotor current).

Power Factor (Cos ϕ nom)

- Power factor at approximately 40% of actuator nominal torque.

Absorbed Power (KW)

- Absorbed electrical power at approximately 40% of actuator nominal torque.

Efficiency (%)

- Referred to the electrical power absorbed by the actuator.

Electric Data

Three-Phase AC

Table 1. Short-Time Duty (S2-15') | Inching Duty (S4-25% | 60 St/h)
3-PH 220 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	SM00	40	0.03	0.04	0.8	0.9	1.1	0.46	0.14	0.19	23.1
ICON_010/30-18	18	SM01	40	0.05	0.07	0.8	1.0	1.4	0.42	0.13	0.17	38.3
ICON_010/30-24	24	SM10	20	0.07	0.10	2.6	3.0	4.3	0.43	0.43	0.57	17.3
ICON_010/30-36	36	SM03	20	0.07	0.10	1.36	1.6	2.33	0.46	0.24	0.32	31.0
ICON_010/30-48	48	SM04	20	0.15	0.19	2.4	4.3	5.0	0.47	0.43	0.58	33.8
ICON_010/30-72	72	SM05	20	0.22	0.29	2.2	4.6	7.8	0.56	0.47	0.63	46.3
ICON_010/30-144	144	SM06	20	0.43	0.58	3.1	4.5	10.8	0.71	0.84	1.12	51.3
ICON_010/90-12	12	SM10	40	0.07	0.10	2.6	3.0	4.3	0.43	0.43	0.57	17.3
ICON_010/90-18	18	SM11	40	0.11	0.15	2.6	2.9	5.0	0.43	0.43	0.57	25.9
ICON_010/90-24	24	SM12	20	0.12	0.17	3.5	3.7	5.0	0.46	0.61	0.82	20.3
ICON_010/90-36	36	SM13	20	0.19	0.25	3.6	4.6	6.3	0.41	0.56	0.75	32.9
ICON_010/90-48	48	SM14	20	0.29	0.39	3.1	3.7	9.2	0.46	0.54	0.73	53.0
ICON_010/90-72	72	SM15	20	0.37	0.49	3.8	5.3	13.3	0.55	0.80	1.07	45.9
ICON_010/90-144	144	SM16	20	0.74	0.99	5.1	8.5	22.6	0.67	1.30	1.74	57.0
ICON_020/180-18	18	SM13	40	0.19	0.25	3.6	4.6	6.3	0.41	0.56	0.75	32.9
ICON_020/180-24	24	SM14	40	0.29	0.39	3.1	3.7	9.2	0.46	0.54	0.73	53.0
ICON_020/180-36	36	SM15	40	0.37	0.49	3.8	5.3	13.3	0.55	0.80	1.07	45.9
ICON_020/180-48	48	SM21	20	0.53	0.71	5.1	8.5	14.1	0.43	0.84	1.12	63.4
ICON_020/180-72	72	SM22	20	0.78	1.05	5.6	11.0	21.0	0.61	1.30	1.74	60.2
ICON_020/180-144	144	SM23	20	1.48	1.98	9.3	15.1	42.4	0.67	2.37	3.18	62.3
ICON_030/360-12	12	SM21	80	0.53	0.71	5.1	8.5	14.1	0.43	0.84	1.12	63.4
ICON_030/360-18	18	SM32	40	0.50	0.67	5.6	7.3	15.1	0.39	0.83	1.12	60.2
ICON_030/360-24	24	SM21	40	0.53	0.71	5.1	8.5	14.1	0.43	0.84	1.12	63.4
ICON_030/360-48	48	SM30	20	1.13	1.51	10.9	18.3	32.6	0.43	1.79	2.39	63.1
ICON_030/360-72	72	SM23	40	1.48	1.98	9.3	15.1	42.4	0.67	2.37	3.18	62.3
ICON_030/360-144	144	SM31	20	3.38	4.53	15.5	31.8	90.8	0.68	4.02	5.38	84.2
ICON_040/720-12	12	SM30	80	1.13	1.51	10.9	18.3	32.6	0.43	1.79	2.39	63.1
ICON_040/720-18	18	SM44	40	0.84	1.12	7.8	13.2	21.6	0.39	1.16	1.55	72.4
ICON_040/720-24	24	SM30	40	1.13	1.51	10.9	18.3	32.6	0.43	1.79	2.39	63.1
ICON_040/720-36	36	SM40	40	1.69	2.26	10.9	21.7	50.9	0.67	2.78	3.73	60.6
ICON_040/720-48	48	SM41	20	1.95	2.61	13.3	27.0	44.9	0.49	2.48	3.33	78.5
ICON_040/720-72	72	SM31	40	3.38	4.53	15.5	31.8	90.8	0.68	4.02	5.38	84.2
ICON_040/720-144	144	SM42	20	5.82	7.80	27.8	56.4	141.4	0.73	7.73	10.36	75.3
ICON_050/1440-12	12	SM41	80	1.95	2.61	13.3	27.0	44.9	0.49	2.48	3.33	78.5
ICON_050/1440-18	18	SM40	80	1.69	2.26	10.9	21.7	50.9	0.67	2.78	3.73	60.6
ICON_050/1440-24	24	SM41	40	1.95	2.61	13.3	27.0	44.9	0.49	2.48	3.33	78.5
ICON_050/1440-36	36	SM43	40	2.89	3.87	16.2	31.8	74.0	0.56	3.46	4.63	83.6
ICON_050/1440-48	48	SM50	20	3.88	5.20	19.8	36.1	114.0	0.61	4.60	6.17	84.3
ICON_050/1440-72	72	SM42	40	5.82	7.80	27.8	56.4	141.4	0.73	7.73	10.36	75.3
ICON_050/1440-144	144	SM51	20	11.66	15.62	48.9	106.9	325.2	0.71	13.23	17.73	88.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 2. 3-PH 230 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	SM00	40	0.03	0.04	0.7	0.8	1.1	0.46	0.13	0.17	23.1
ICON_010/30-18	18	SM01	40	0.05	0.07	0.8	1.0	1.5	0.42	0.13	0.18	38.3
ICON_010/30-24	24	SM10	20	0.07	0.10	2.4	3.0	4.5	0.43	0.41	0.55	17.3
ICON_010/30-36	36	SM03	20	0.07	0.10	1.3	1.56	2.44	0.46	0.24	0.32	31.0
ICON_010/30-48	48	SM04	20	0.15	0.20	2.3	4.2	5.2	0.47	0.43	0.58	33.8
ICON_010/30-72	72	SM05	20	0.22	0.29	2.1	4.5	8.2	0.56	0.47	0.63	46.3
ICON_010/30-144	144	SM06	20	0.44	0.58	3.0	4.4	11.3	0.71	0.85	1.14	51.3
ICON_010/90-12	12	SM10	40	0.07	0.10	2.4	3.0	4.5	0.43	0.41	0.55	17.3
ICON_010/90-18	18	SM11	40	0.11	0.14	2.4	2.8	5.2	0.43	0.41	0.55	25.9
ICON_010/90-24	24	SM12	20	0.12	0.16	3.3	3.7	5.2	0.46	0.60	0.81	20.3
ICON_010/90-36	36	SM13	20	0.19	0.25	3.5	4.5	6.6	0.41	0.57	0.77	32.9
ICON_010/90-48	48	SM14	20	0.29	0.39	3.0	3.7	9.6	0.46	0.55	0.74	53.0
ICON_010/90-72	72	SM15	20	0.37	0.50	3.7	5.2	13.9	0.55	0.81	1.09	45.9
ICON_010/90-144	144	SM16	20	0.74	0.99	4.9	8.4	23.7	0.67	1.31	1.75	56.5
ICON_020/180-18	18	SM13	40	0.19	0.25	3.5	4.5	6.6	0.41	0.57	0.77	32.9
ICON_020/180-24	24	SM14	40	0.29	0.39	3.0	3.7	9.6	0.46	0.55	0.74	53.0
ICON_020/180-36	36	SM15	40	0.37	0.50	3.7	5.2	13.9	0.55	0.81	1.09	45.9
ICON_020/180-48	48	SM21	20	0.53	0.71	4.9	8.4	14.8	0.43	0.84	1.12	63.4
ICON_020/180-72	72	SM22	20	0.79	1.06	5.4	10.8	21.9	0.61	1.31	1.76	60.2
ICON_020/180-144	144	SM23	20	1.48	1.98	8.9	14.8	44.4	0.67	2.38	3.18	62.3
ICON_030/360-12	12	SM21	80	0.53	0.71	4.9	8.4	14.8	0.43	0.84	1.12	63.4
ICON_030/360-18	18	SM32	40	0.51	0.68	5.4	7.1	15.8	0.39	0.84	1.12	60.2
ICON_030/360-24	24	SM21	40	0.53	0.71	4.9	8.4	14.8	0.43	0.84	1.12	63.4
ICON_030/360-48	48	SM30	20	1.12	1.51	10.4	17.9	34.1	0.43	1.78	2.39	63.1
ICON_030/360-72	72	SM23	40	1.48	1.98	8.9	14.8	44.4	0.67	2.38	3.18	62.3
ICON_030/360-144	144	SM31	20	3.38	4.52	14.8	31.1	95.0	0.68	4.01	5.37	84.2
ICON_040/720-12	12	SM30	80	1.12	1.51	10.4	17.9	34.1	0.43	1.78	2.39	63.1
ICON_040/720-18	18	SM44	40	0.84	1.13	7.5	12.9	22.6	0.39	1.17	1.56	72.4
ICON_040/720-24	24	SM30	40	1.12	1.51	10.4	17.9	34.1	0.43	1.78	2.39	63.1
ICON_040/720-36	36	SM40	40	1.68	2.25	10.4	21.2	53.2	0.67	2.78	3.72	60.6
ICON_040/720-48	48	SM41	20	1.95	2.61	12.7	26.4	47.0	0.49	2.48	3.32	78.5
ICON_040/720-72	72	SM31	40	3.38	4.52	14.8	31.1	95.0	0.68	4.01	5.37	84.2
ICON_040/720-144	144	SM42	20	5.82	7.81	26.6	55.1	147.8	0.73	7.74	10.37	75.3
ICON_050/1440-12	12	SM41	80	1.95	2.61	12.7	26.4	47.0	0.49	2.48	3.32	78.5
ICON_050/1440-18	18	SM40	80	1.68	2.25	10.4	21.2	53.2	0.67	2.78	3.72	60.6
ICON_050/1440-24	24	SM41	40	1.95	2.61	12.7	26.4	47.0	0.49	2.48	3.32	78.5
ICON_050/1440-36	36	SM43	40	2.89	3.87	15.5	31.1	77.4	0.56	3.46	4.63	83.6
ICON_050/1440-48	48	SM50	20	3.89	5.22	19.0	35.3	119.1	0.61	4.62	6.19	84.3
ICON_050/1440-72	72	SM42	40	5.82	7.81	26.6	55.1	147.8	0.73	7.74	10.37	75.3
ICON_050/1440-144	144	SM51	20	11.66	15.63	46.8	104.5	340.0	0.71	13.24	17.74	88.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 3. 3-PH 240 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	SM00	40	0.03	0.04	0.7	0.8	1.2	0.46	0.13	0.18	23.1
ICON_010/30-18	18	SM01	40	0.05	0.06	0.7	0.9	1.5	0.42	0.12	0.16	38.3
ICON_010/30-24	24	SM10	20	0.07	0.10	2.3	2.9	4.7	0.43	0.41	0.55	17.3
ICON_010/30-36	36	SM03	20	0.07	0.10	1.25	1.53	2.54	0.46	0.24	0.32	31.0
ICON_010/30-48	48	SM04	20	0.15	0.19	2.2	4.1	5.4	0.47	0.43	0.58	33.8
ICON_010/30-72	72	SM05	20	0.22	0.29	2.0	4.4	8.5	0.56	0.47	0.62	46.3
ICON_010/30-144	144	SM06	20	0.42	0.57	2.8	4.3	11.8	0.71	0.83	1.11	51.3
ICON_010/90-12	12	SM10	40	0.07	0.10	2.3	2.9	4.7	0.43	0.41	0.55	17.3
ICON_010/90-18	18	SM11	40	0.11	0.14	2.3	2.7	5.4	0.43	0.41	0.55	25.9
ICON_010/90-24	24	SM12	20	0.12	0.17	3.2	3.6	5.4	0.46	0.61	0.82	20.3
ICON_010/90-36	36	SM13	20	0.19	0.25	3.3	4.4	6.9	0.41	0.56	0.75	32.9
ICON_010/90-48	48	SM14	20	0.28	0.38	2.8	3.6	10.0	0.46	0.54	0.72	53.0
ICON_010/90-72	72	SM15	20	0.37	0.49	3.5	5.1	14.5	0.55	0.80	1.07	45.9
ICON_010/90-144	144	SM16	20	0.74	0.99	4.7	8.2	24.7	0.67	1.31	1.75	56.5
ICON_020/180-18	18	SM13	40	0.19	0.25	3.3	4.4	6.9	0.41	0.56	0.75	32.9
ICON_020/180-24	24	SM14	40	0.28	0.38	2.8	3.6	10.0	0.46	0.54	0.72	53.0
ICON_020/180-36	36	SM15	40	0.37	0.49	3.5	5.1	14.5	0.55	0.80	1.07	45.9
ICON_020/180-48	48	SM21	20	0.53	0.71	4.7	8.2	15.4	0.43	0.84	1.13	63.4
ICON_020/180-72	72	SM22	20	0.79	1.06	5.2	10.6	22.9	0.61	1.32	1.77	60.2
ICON_020/180-144	144	SM23	20	1.47	1.98	8.5	14.5	46.3	0.67	2.37	3.17	62.3
ICON_030/360-12	12	SM21	80	0.53	0.71	4.7	8.2	15.4	0.43	0.84	1.13	63.4
ICON_030/360-18	18	SM32	40	0.51	0.68	5.2	7.0	16.5	0.39	0.84	1.13	60.2
ICON_030/360-24	24	SM21	40	0.53	0.71	4.7	8.2	15.4	0.43	0.84	1.13	63.4
ICON_030/360-48	48	SM30	20	1.13	1.51	10.0	17.5	35.6	0.43	1.79	2.40	63.1
ICON_030/360-72	72	SM23	40	1.47	1.98	8.5	14.5	46.3	0.67	2.37	3.17	62.3
ICON_030/360-144	144	SM31	20	3.38	4.53	14.2	30.5	99.1	0.68	4.01	5.38	84.2
ICON_040/720-12	12	SM30	80	1.13	1.51	10.0	17.5	35.6	0.43	1.79	2.40	63.1
ICON_040/720-18	18	SM44	40	0.85	1.13	7.2	12.6	23.6	0.39	1.17	1.56	72.4
ICON_040/720-24	24	SM30	40	1.13	1.51	10.0	17.5	35.6	0.43	1.79	2.40	63.1
ICON_040/720-36	36	SM40	40	1.69	2.26	10.0	20.8	55.5	0.67	2.79	3.73	60.6
ICON_040/720-48	48	SM41	20	1.95	2.61	12.2	25.9	49.0	0.49	2.49	3.33	78.5
ICON_040/720-72	72	SM31	40	3.38	4.53	14.2	30.5	99.1	0.68	4.01	5.38	84.2
ICON_040/720-144	144	SM42	20	5.83	7.81	25.5	54.0	154.3	0.73	7.74	10.37	75.3
ICON_050/1440-12	12	SM41	80	1.95	2.61	12.2	25.9	49.0	0.49	2.49	3.33	78.5
ICON_050/1440-18	18	SM40	80	1.69	2.26	10.0	20.8	55.5	0.67	2.79	3.73	60.6
ICON_050/1440-24	24	SM41	40	1.95	2.61	12.2	25.9	49.0	0.49	2.49	3.33	78.5
ICON_050/1440-36	36	SM43	40	2.88	3.86	14.8	30.5	80.8	0.56	3.45	4.62	83.6
ICON_050/1440-48	48	SM50	20	3.89	5.21	18.2	34.6	124.3	0.61	4.62	6.18	84.3
ICON_050/1440-72	72	SM42	40	5.83	7.81	25.5	54.0	154.3	0.73	7.74	10.37	75.3
ICON_050/1440-144	144	SM51	20	11.65	15.61	44.8	102.3	354.8	0.71	13.22	17.72	88.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 4. 3-PH 380 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	SM00	40	0.03	0.04	0.4	0.5	0.6	0.46	0.12	0.16	23.1
ICON_010/30-18	18	SM01	40	0.05	0.07	0.5	0.6	0.8	0.42	0.14	0.19	38.3
ICON_010/30-24	24	SM10	20	0.07	0.10	1.5	1.7	2.5	0.43	0.42	0.57	17.3
ICON_010/30-36	36	SM03	20	0.07	0.10	0.79	0.92	1.48	0.46	0.24	0.32	31.0
ICON_010/30-72	72	SM05	20	0.22	0.30	1.3	2.7	4.5	0.56	0.48	0.64	46.3
ICON_010/30-144	144	SM06	20	0.43	0.58	1.8	2.6	6.2	0.71	0.84	1.13	51.3
ICON_010/90-12	12	SM10	40	0.07	0.10	1.5	1.7	2.5	0.43	0.42	0.57	17.3
ICON_010/90-18	18	SM11	40	0.11	0.15	1.5	1.6	2.9	0.43	0.42	0.57	25.9
ICON_010/90-24	24	SM12	20	0.12	0.16	2.0	2.2	2.9	0.46	0.61	0.81	20.3
ICON_010/90-36	36	SM13	20	0.19	0.25	2.1	2.7	3.6	0.41	0.57	0.76	32.9
ICON_010/90-48	48	SM14	20	0.29	0.39	1.8	2.2	5.2	0.46	0.54	0.73	53.0
ICON_010/90-72	72	SM15	20	0.37	0.49	2.2	3.1	7.6	0.55	0.80	1.07	45.9
ICON_010/90-144	144	SM16	20	0.75	1.00	3.0	4.9	12.9	0.67	1.32	1.77	56.5
ICON_020/180-18	18	SM13	40	0.19	0.25	2.1	2.7	3.6	0.41	0.57	0.76	32.9
ICON_020/180-24	24	SM14	40	0.29	0.39	1.8	2.2	5.2	0.46	0.54	0.73	53.0
ICON_020/180-36	36	SM15	40	0.37	0.49	2.2	3.1	7.6	0.55	0.80	1.07	45.9
ICON_020/180-48	48	SM21	20	0.54	0.72	3.0	4.9	8.1	0.43	0.85	1.14	63.4
ICON_020/180-72	72	SM22	20	0.80	1.08	3.3	6.4	12.0	0.61	1.32	1.78	60.7
ICON_020/180-144	144	SM23	20	1.48	1.99	5.4	8.7	24.2	0.67	2.38	3.19	62.3
ICON_030/360-12	12	SM21	80	0.54	0.72	3.0	4.9	8.1	0.43	0.85	1.14	63.4
ICON_030/360-18	18	SM32	40	0.51	0.68	3.3	4.2	8.7	0.39	0.84	1.12	61.0
ICON_030/360-24	24	SM21	40	0.54	0.72	3.0	4.9	8.1	0.43	0.85	1.14	63.4
ICON_030/360-48	48	SM30	20	1.13	1.51	6.3	10.6	18.6	0.43	1.78	2.39	63.1
ICON_030/360-72	72	SM23	40	1.48	1.99	5.4	8.7	24.2	0.67	2.38	3.19	62.3
ICON_030/360-144	144	SM31	20	3.39	4.54	9.0	18.4	51.9	0.68	4.03	5.40	84.2
ICON_040/720-12	12	SM30	80	1.13	1.51	6.3	10.6	18.6	0.43	1.78	2.39	63.1
ICON_040/720-18	18	SM44	40	0.84	1.12	4.5	7.6	12.4	0.39	1.15	1.55	72.4
ICON_040/720-24	24	SM30	40	1.13	1.51	6.3	10.6	18.6	0.43	1.78	2.39	63.1
ICON_040/720-36	36	SM40	40	1.68	2.26	6.3	12.5	29.1	0.67	2.78	3.72	60.6
ICON_040/720-48	48	SM41	20	1.95	2.61	7.7	15.6	25.7	0.49	2.48	3.33	78.5
ICON_040/720-72	72	SM31	40	3.39	4.54	9.0	18.4	51.9	0.68	4.03	5.40	84.2
ICON_040/720-144	144	SM42	20	5.82	7.79	16.1	32.5	80.8	0.73	7.74	10.37	75.2
ICON_050/1440-12	12	SM41	80	1.95	2.61	7.7	15.6	25.7	0.49	2.48	3.33	78.5
ICON_050/1440-18	18	SM40	80	1.68	2.26	6.3	12.5	29.1	0.67	2.78	3.72	60.6
ICON_050/1440-24	24	SM41	40	1.95	2.61	7.7	15.6	25.7	0.49	2.48	3.33	78.5
ICON_050/1440-36	36	SM43	40	2.90	3.88	9.4	18.4	42.3	0.56	3.46	4.64	83.6
ICON_050/1440-48	48	SM50	20	3.89	5.22	11.5	20.8	65.1	0.61	4.62	6.19	84.3
ICON_050/1440-72	72	SM42	40	5.82	7.79	16.1	32.5	80.8	0.73	7.74	10.37	75.2
ICON_050/1440-144	144	SM51	20	11.65	15.61	28.3	61.7	185.7	0.71	13.22	17.72	88.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 5. 3-PH 400 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	SM00	40	0.03	0.04	0.4	0.5	0.7	0.46	0.13	0.17	23.1
ICON_010/30-18	18	SM01	40	0.04	0.06	0.4	0.6	0.9	0.42	0.12	0.16	38.3
ICON_010/30-24	24	SM10	20	0.07	0.10	1.4	1.7	2.6	0.43	0.42	0.56	17.3
ICON_010/30-36	36	SM03	20	0.07	0.10	0.75	0.9	1.4	0.46	0.24	0.32	31.0
ICON_010/30-48	48	SM04	20	0.14	0.19	1.3	2.4	3.0	0.47	0.42	0.57	33.8
ICON_010/30-72	72	SM05	20	0.22	0.29	1.2	2.6	4.7	0.56	0.47	0.62	46.3
ICON_010/30-144	144	SM06	20	0.43	0.57	1.7	2.5	6.5	0.71	0.84	1.12	51.3
ICON_010/90-12	12	SM10	40	0.07	0.10	1.4	1.7	2.6	0.43	0.42	0.56	17.3
ICON_010/90-18	18	SM11	40	0.11	0.14	1.4	1.6	3.0	0.43	0.42	0.56	25.9
ICON_010/90-24	24	SM12	20	0.12	0.16	1.9	2.1	3.0	0.46	0.61	0.81	20.3
ICON_010/90-36	36	SM13	20	0.19	0.25	2.0	2.6	3.8	0.41	0.57	0.76	32.9
ICON_010/90-48	48	SM14	20	0.29	0.38	1.7	2.1	5.5	0.46	0.54	0.73	53.0
ICON_010/90-72	72	SM15	20	0.37	0.49	2.1	3.0	8.0	0.55	0.80	1.07	45.9
ICON_010/90-144	144	SM16	20	0.73	0.98	2.8	4.8	13.6	0.67	1.30	1.74	56.5
ICON_020/180-18	18	SM13	40	0.19	0.25	2.0	2.6	3.8	0.41	0.57	0.76	32.9
ICON_020/180-24	24	SM14	40	0.29	0.38	1.7	2.1	5.5	0.46	0.54	0.73	53.0
ICON_020/180-36	36	SM15	40	0.37	0.49	2.1	3.0	8.0	0.55	0.80	1.07	45.9
ICON_020/180-48	48	SM21	20	0.53	0.71	2.8	4.8	8.5	0.43	0.83	1.12	63.4
ICON_020/180-72	72	SM22	20	0.79	1.06	3.1	6.2	12.6	0.61	1.31	1.76	60.2
ICON_020/180-144	144	SM23	20	1.47	1.98	5.1	8.5	25.5	0.67	2.37	3.17	62.3
ICON_030/360-12	12	SM21	80	0.53	0.71	2.8	4.8	8.5	0.43	0.83	1.12	63.4
ICON_030/360-18	18	SM32	40	0.51	0.68	3.1	4.1	9.1	0.39	0.83	1.11	61.0
ICON_030/360-24	24	SM21	40	0.53	0.71	2.8	4.8	8.5	0.43	0.83	1.12	63.4
ICON_030/360-48	48	SM30	20	1.13	1.51	6.0	10.3	19.6	0.43	1.79	2.40	63.1
ICON_030/360-72	72	SM23	40	1.47	1.98	5.1	8.5	25.5	0.67	2.37	3.17	62.3
ICON_030/360-144	144	SM31	20	3.37	4.52	8.5	17.9	54.6	0.68	4.00	5.37	84.2
ICON_040/720-12	12	SM30	80	1.13	1.51	6.0	10.3	19.6	0.43	1.79	2.40	63.1
ICON_040/720-18	18	SM44	40	0.84	1.13	4.3	7.4	13.0	0.39	1.16	1.55	72.4
ICON_040/720-24	24	SM30	40	1.13	1.51	6.0	10.3	19.6	0.43	1.79	2.40	63.1
ICON_040/720-36	36	SM40	40	1.69	2.26	6.0	12.2	30.6	0.67	2.79	3.73	60.6
ICON_040/720-48	48	SM41	20	1.95	2.61	7.3	15.2	27.0	0.49	2.48	3.32	78.5
ICON_040/720-72	72	SM31	40	3.37	4.52	8.5	17.9	54.6	0.68	4.00	5.37	84.2
ICON_040/720-144	144	SM42	20	5.83	7.81	15.3	31.7	85.0	0.73	7.74	10.37	75.3
ICON_050/1440-12	12	SM41	80	1.95	2.61	7.3	15.2	27.0	0.49	2.48	3.32	78.5
ICON_050/1440-18	18	SM40	80	1.69	2.26	6.0	12.2	30.6	0.67	2.79	3.73	60.6
ICON_050/1440-24	24	SM41	40	1.95	2.61	7.3	15.2	27.0	0.49	2.48	3.32	78.5
ICON_050/1440-36	36	SM43	40	2.89	3.87	8.9	17.9	44.5	0.56	3.45	4.63	83.6
ICON_050/1440-48	48	SM50	20	3.88	5.20	10.9	20.3	68.5	0.61	4.61	6.17	84.3
ICON_050/1440-72	72	SM42	40	5.83	7.81	15.3	31.7	85.0	0.73	7.74	10.37	75.3
ICON_050/1440-144	144	SM51	20	11.66	15.62	26.9	60.1	195.5	0.71	13.23	17.73	88.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 6. 3-PH 415 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	SM00	40	0.03	0.04	0.4	0.5	0.7	0.46	0.13	0.18	23.1
ICON_010/30-18	18	SM01	40	0.05	0.06	0.4	0.5	0.9	0.42	0.12	0.16	38.3
ICON_010/30-24	24	SM10	20	0.07	0.10	1.4	1.7	2.7	0.43	0.43	0.58	17.3
ICON_010/30-36	36	SM03	20	0.07	0.10	0.72	0.89	1.38	0.46	0.24	0.32	31.0
ICON_010/30-48	48	SM04	20	0.15	0.20	1.3	2.4	3.1	0.47	0.44	0.59	33.8
ICON_010/30-72	72	SM05	20	0.22	0.30	1.2	2.6	4.9	0.56	0.48	0.65	46.3
ICON_010/30-144	144	SM06	20	0.42	0.56	1.6	2.5	6.7	0.71	0.82	1.09	51.3
ICON_010/90-12	12	SM10	40	0.07	0.10	1.4	1.7	2.7	0.43	0.43	0.58	17.3
ICON_010/90-18	18	SM11	40	0.11	0.15	1.4	1.6	3.1	0.43	0.43	0.58	25.9
ICON_010/90-24	24	SM12	20	0.12	0.16	1.8	2.1	3.1	0.46	0.60	0.80	20.3
ICON_010/90-36	36	SM13	20	0.18	0.25	1.9	2.6	3.9	0.41	0.56	0.75	32.9
ICON_010/90-48	48	SM14	20	0.28	0.38	1.6	2.1	5.7	0.46	0.53	0.71	53.0
ICON_010/90-72	72	SM15	20	0.37	0.49	2.0	3.0	8.3	0.55	0.79	1.06	46.5
ICON_010/90-144	144	SM16	20	0.73	0.98	2.7	4.7	14.1	0.67	1.30	1.74	56.5
ICON_020/180-18	18	SM13	40	0.18	0.25	1.9	2.6	3.9	0.41	0.56	0.75	32.9
ICON_020/180-24	24	SM14	40	0.28	0.38	1.6	2.1	5.7	0.46	0.53	0.71	53.0
ICON_020/180-36	36	SM15	40	0.37	0.49	2.0	3.0	8.3	0.55	0.79	1.06	46.5
ICON_020/180-48	48	SM21	20	0.53	0.71	2.7	4.7	8.8	0.43	0.83	1.12	63.4
ICON_020/180-72	72	SM22	20	0.79	1.06	3.0	6.1	13.1	0.61	1.32	1.76	60.2
ICON_020/180-144	144	SM23	20	1.47	1.97	4.9	8.3	26.5	0.67	2.36	3.16	62.3
ICON_030/360-12	12	SM21	80	0.53	0.71	2.7	4.7	8.8	0.43	0.83	1.12	63.4
ICON_030/360-18	18	SM32	40	0.51	0.68	3.0	4.0	9.4	0.39	0.83	1.11	61.0
ICON_030/360-24	24	SM21	40	0.53	0.71	2.7	4.7	8.8	0.43	0.83	1.12	63.4
ICON_030/360-48	48	SM30	20	1.13	1.52	5.8	10.1	20.3	0.43	1.79	2.40	63.1
ICON_030/360-72	72	SM23	40	1.47	1.97	4.9	8.3	26.5	0.67	2.36	3.16	62.3
ICON_030/360-144	144	SM31	20	3.37	4.52	8.2	17.6	56.7	0.68	4.01	5.37	84.2
ICON_040/720-12	12	SM30	80	1.13	1.52	5.8	10.1	20.3	0.43	1.79	2.40	63.1
ICON_040/720-18	18	SM44	40	0.84	1.12	4.1	7.3	13.5	0.39	1.15	1.54	73.0
ICON_040/720-24	24	SM30	40	1.13	1.52	5.8	10.1	20.3	0.43	1.79	2.40	63.1
ICON_040/720-36	36	SM40	40	1.69	2.27	5.8	12.0	31.8	0.67	2.79	3.74	60.6
ICON_040/720-48	48	SM41	20	1.93	2.58	7.0	14.9	28.0	0.49	2.47	3.30	78.2
ICON_040/720-72	72	SM31	40	3.37	4.52	8.2	17.6	56.7	0.68	4.01	5.37	84.2
ICON_040/720-144	144	SM42	20	5.84	7.83	14.8	31.1	88.2	0.73	7.77	10.41	75.2
ICON_050/1440-12	12	SM41	80	1.93	2.58	7.0	14.9	28.0	0.49	2.47	3.30	78.2
ICON_050/1440-18	18	SM40	80	1.69	2.27	5.8	12.0	31.8	0.67	2.79	3.74	60.6
ICON_050/1440-24	24	SM41	40	1.93	2.58	7.0	14.9	28.0	0.49	2.47	3.30	78.2
ICON_050/1440-36	36	SM43	40	2.89	3.88	8.6	17.6	46.2	0.56	3.46	4.64	83.6
ICON_050/1440-48	48	SM50	20	3.88	5.20	10.5	19.9	71.1	0.61	4.60	6.17	84.3
ICON_050/1440-72	72	SM42	40	5.84	7.83	14.8	31.1	88.2	0.73	7.77	10.41	75.2
ICON_050/1440-144	144	SM51	20	11.65	15.60	25.9	59.0	202.8	0.71	13.22	17.71	88.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 7. 3-PH 440 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	SM00	40	0.03	0.04	0.4	0.4	0.6	0.46	0.14	0.19	23.1
ICON_010/30-18	18	SM01	40	0.05	0.07	0.4	0.5	0.8	0.42	0.13	0.17	38.3
ICON_010/30-24	24	SM10	20	0.07	0.10	1.3	1.6	2.4	0.43	0.43	0.57	17.3
ICON_010/30-36	36	SM03	20	0.07	0.10	0.68	0.82	1.27	0.46	0.24	0.32	31.0
ICON_010/30-48	48	SM04	20	0.15	0.19	1.2	2.2	2.7	0.47	0.43	0.58	33.8
ICON_010/30-72	72	SM05	20	0.22	0.29	1.1	2.4	4.3	0.56	0.47	0.63	46.3
ICON_010/30-144	144	SM06	20	0.44	0.60	1.6	2.3	5.9	0.71	0.87	1.16	51.3
ICON_010/90-12	12	SM10	40	0.07	0.10	1.3	1.6	2.4	0.43	0.43	0.57	17.3
ICON_010/90-18	18	SM11	40	0.11	0.15	1.3	1.5	2.7	0.43	0.43	0.57	25.9
ICON_010/90-24	24	SM12	20	0.12	0.16	1.7	1.9	2.7	0.46	0.60	0.80	20.3
ICON_010/90-36	36	SM13	20	0.19	0.25	1.8	2.4	3.5	0.41	0.56	0.75	32.9
ICON_010/90-48	48	SM14	20	0.30	0.40	1.6	1.9	5.0	0.46	0.56	0.75	53.0
ICON_010/90-72	72	SM15	20	0.37	0.49	1.9	2.7	7.3	0.55	0.80	1.07	45.9
ICON_010/90-144	144	SM16	20	0.75	1.01	2.6	4.4	12.4	0.67	1.33	1.78	56.5
ICON_020/180-18	18	SM13	40	0.19	0.25	1.8	2.4	3.5	0.41	0.56	0.75	32.9
ICON_020/180-24	24	SM14	40	0.30	0.40	1.6	1.9	5.0	0.46	0.56	0.75	53.0
ICON_020/180-36	36	SM15	40	0.37	0.49	1.9	2.7	7.3	0.55	0.80	1.07	45.9
ICON_020/180-48	48	SM21	20	0.54	0.72	2.6	4.4	7.7	0.43	0.85	1.14	63.4
ICON_020/180-72	72	SM22	20	0.78	1.05	2.8	5.6	11.5	0.61	1.30	1.74	60.2
ICON_020/180-144	144	SM23	20	1.46	1.96	4.6	7.7	23.2	0.67	2.35	3.15	62.3
ICON_030/360-12	12	SM21	80	0.54	0.72	2.6	4.4	7.7	0.43	0.85	1.14	63.4
ICON_030/360-18	18	SM32	40	0.50	0.67	2.8	3.7	8.3	0.39	0.83	1.12	60.2
ICON_030/360-24	24	SM21	40	0.54	0.72	2.6	4.4	7.7	0.43	0.85	1.14	63.4
ICON_030/360-48	48	SM30	20	1.14	1.52	5.5	9.4	17.8	0.43	1.80	2.42	63.1
ICON_030/360-72	72	SM23	40	1.46	1.96	4.6	7.7	23.2	0.67	2.35	3.15	62.3
ICON_030/360-144	144	SM31	20	3.36	4.50	7.7	16.3	49.6	0.68	3.99	5.35	84.2
ICON_040/720-12	12	SM30	80	1.14	1.52	5.5	9.4	17.8	0.43	1.80	2.42	63.1
ICON_040/720-18	18	SM44	40	0.84	1.12	3.9	6.7	11.8	0.39	1.16	1.55	72.4
ICON_040/720-24	24	SM30	40	1.14	1.52	5.5	9.4	17.8	0.43	1.80	2.42	63.1
ICON_040/720-36	36	SM40	40	1.70	2.28	5.5	11.1	27.8	0.67	2.81	3.76	60.6
ICON_040/720-48	48	SM41	20	1.93	2.58	6.6	13.8	24.6	0.49	2.46	3.30	78.2
ICON_040/720-72	72	SM31	40	3.36	4.50	7.7	16.3	49.6	0.68	3.99	5.35	84.2
ICON_040/720-144	144	SM42	20	5.82	7.80	13.9	28.8	77.3	0.73	7.73	10.36	75.3
ICON_050/1440-12	12	SM41	80	1.93	2.58	6.6	13.8	24.6	0.49	2.46	3.30	78.2
ICON_050/1440-18	18	SM40	80	1.70	2.28	5.5	11.1	27.8	0.67	2.81	3.76	60.6
ICON_050/1440-24	24	SM41	40	1.93	2.58	6.6	13.8	24.6	0.49	2.46	3.30	78.2
ICON_050/1440-36	36	SM43	40	2.89	3.87	8.1	16.3	40.5	0.56	3.46	4.63	83.6
ICON_050/1440-48	48	SM50	20	3.88	5.20	9.9	18.5	62.3	0.61	4.60	6.17	84.3
ICON_050/1440-72	72	SM42	40	5.82	7.80	13.9	28.8	77.3	0.73	7.73	10.36	75.3
ICON_050/1440-144	144	SM51	20	11.68	15.65	24.5	54.6	177.7	0.71	13.26	17.76	88.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 8. 3-PH 500 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	SM00	40	0.03	0.04	0.3	0.4	0.5	0.46	0.12	0.16	23.1
ICON_010/30-18	18	SM01	40	0.06	0.07	0.4	0.4	0.7	0.42	0.15	0.19	38.3
ICON_010/30-24	24	SM10	20	0.07	0.09	1.1	1.4	2.1	0.43	0.41	0.55	17.3
ICON_010/30-36	36	SM03	20	0.07	0.10	0.06	0.72	1.12	0.46	0.24	0.32	31.0
ICON_010/30-48	48	SM04	20	0.14	0.18	1.0	1.9	2.4	0.47	0.41	0.55	33.8
ICON_010/30-72	72	SM05	20	0.22	0.30	1.0	2.1	3.8	0.56	0.48	0.65	46.3
ICON_010/30-144	144	SM06	20	0.44	0.59	1.4	2.0	5.2	0.71	0.86	1.15	51.3
ICON_010/90-12	12	SM10	40	0.07	0.09	1.1	1.4	2.1	0.43	0.41	0.55	17.3
ICON_010/90-18	18	SM11	40	0.11	0.14	1.1	1.3	2.4	0.43	0.41	0.55	25.9
ICON_010/90-24	24	SM12	20	0.12	0.16	1.5	1.7	2.4	0.46	0.60	0.80	20.3
ICON_010/90-36	36	SM13	20	0.19	0.25	1.6	2.1	3.0	0.41	0.57	0.76	32.9
ICON_010/90-48	48	SM14	20	0.30	0.40	1.4	1.7	4.4	0.46	0.56	0.75	53.0
ICON_010/90-72	72	SM15	20	0.37	0.50	1.7	2.4	6.4	0.55	0.81	1.09	45.9
ICON_010/90-144	144	SM16	20	0.72	0.97	2.2	3.8	10.9	0.67	1.28	1.71	56.5
ICON_020/180-18	18	SM13	40	0.19	0.25	1.6	2.1	3.0	0.41	0.57	0.76	32.9
ICON_020/180-24	24	SM14	40	0.30	0.40	1.4	1.7	4.4	0.46	0.56	0.75	53.0
ICON_020/180-36	36	SM15	40	0.37	0.50	1.7	2.4	6.4	0.55	0.81	1.09	45.9
ICON_020/180-48	48	SM21	20	0.52	0.70	2.2	3.8	6.8	0.43	0.82	1.10	63.4
ICON_020/180-72	72	SM22	20	0.80	1.07	2.5	5.0	10.1	0.61	1.32	1.77	60.2
ICON_020/180-144	144	SM23	20	1.48	1.99	4.1	6.8	20.4	0.67	2.38	3.19	62.3
ICON_030/360-12	12	SM21	80	0.52	0.70	2.2	3.8	6.8	0.43	0.82	1.10	63.4
ICON_030/360-18	18	SM32	40	0.51	0.68	2.5	3.3	7.3	0.39	0.83	1.12	61.0
ICON_030/360-24	24	SM21	40	0.52	0.70	2.2	3.8	6.8	0.43	0.82	1.10	63.4
ICON_030/360-48	48	SM30	20	1.13	1.51	4.8	8.2	15.7	0.43	1.79	2.40	63.1
ICON_030/360-72	72	SM23	40	1.48	1.99	4.1	6.8	20.4	0.67	2.38	3.19	62.3
ICON_030/360-144	144	SM31	20	3.37	4.52	6.8	14.3	43.7	0.68	4.00	5.37	84.2
ICON_040/720-12	12	SM30	80	1.13	1.51	4.8	8.2	15.7	0.43	1.79	2.40	63.1
ICON_040/720-18	18	SM44	40	0.83	1.11	3.4	5.9	10.4	0.39	1.15	1.54	72.4
ICON_040/720-24	24	SM30	40	1.13	1.51	4.8	8.2	15.7	0.43	1.79	2.40	63.1
ICON_040/720-36	36	SM40	40	1.69	2.26	4.8	9.8	24.5	0.67	2.79	3.73	60.6
ICON_040/720-48	48	SM41	20	1.93	2.59	5.8	12.2	21.6	0.49	2.46	3.30	78.5
ICON_040/720-72	72	SM31	40	3.37	4.52	6.8	14.3	43.7	0.68	4.00	5.37	84.2
ICON_040/720-144	144	SM42	20	5.81	7.78	12.2	25.4	68.0	0.73	7.71	10.34	75.3
ICON_050/1440-12	12	SM41	80	1.93	2.59	5.8	12.2	21.6	0.49	2.46	3.30	78.5
ICON_050/1440-18	18	SM40	80	1.69	2.26	4.8	9.8	24.5	0.67	2.79	3.73	60.6
ICON_050/1440-24	24	SM41	40	1.93	2.59	5.8	12.2	21.6	0.49	2.46	3.30	78.5
ICON_050/1440-36	36	SM43	40	2.88	3.86	7.1	14.3	35.6	0.56	3.44	4.61	83.6
ICON_050/1440-48	48	SM50	20	3.87	5.19	8.7	16.2	54.8	0.61	4.60	6.16	84.3
ICON_050/1440-72	72	SM42	40	5.81	7.78	12.2	25.4	68.0	0.73	7.71	10.34	75.3
ICON_050/1440-144	144	SM51	20	11.65	15.61	21.5	48.1	156.4	0.71	13.22	17.71	88.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 9. 3-PH 660 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	SM00	40	0.04	0.05	0.3	0.3	0.4	0.46	0.16	0.21	23.1
ICON_010/30-18	18	SM01	40	0.05	0.07	0.3	0.3	0.5	0.42	0.14	0.19	35.4
ICON_010/30-24	24	SM10	20	0.08	0.10	0.9	1.0	1.6	0.43	0.44	0.59	17.3
ICON_010/30-36	36	SM03	20	0.07	0.10	0.46	0.54	0.85	0.46	0.24	0.32	31.0
ICON_010/30-48	48	SM04	20	0.15	0.19	0.8	1.5	1.8	0.47	0.43	0.58	33.8
ICON_010/30-72	72	SM05	20	0.21	0.28	0.7	1.6	2.9	0.56	0.45	0.60	46.3
ICON_010/30-144	144	SM06	20	0.42	0.56	1.0	1.5	3.9	0.71	0.81	1.09	51.3
ICON_010/90-12	12	SM10	40	0.08	0.10	0.9	1.0	1.6	0.43	0.44	0.59	17.3
ICON_010/90-18	18	SM11	40	0.11	0.15	0.9	1.0	1.8	0.43	0.44	0.59	25.9
ICON_010/90-24	24	SM12	20	0.13	0.17	1.2	1.3	1.8	0.46	0.63	0.85	20.3
ICON_010/90-36	36	SM13	20	0.19	0.25	1.2	1.6	2.3	0.41	0.56	0.75	32.9
ICON_010/90-48	48	SM14	20	0.28	0.37	1.0	1.3	3.3	0.46	0.53	0.70	53.0
ICON_010/90-72	72	SM15	20	0.38	0.51	1.3	1.8	4.9	0.55	0.82	1.10	46.5
ICON_010/90-144	144	SM16	20	0.74	0.99	1.7	2.9	8.2	0.67	1.30	1.74	56.5
ICON_020/180-18	18	SM13	40	0.19	0.25	1.2	1.6	2.3	0.41	0.56	0.75	32.9
ICON_020/180-24	24	SM14	40	0.28	0.37	1.0	1.3	3.3	0.46	0.53	0.70	53.0
ICON_020/180-36	36	SM15	40	0.38	0.51	1.3	1.8	4.9	0.55	0.82	1.10	46.5
ICON_020/180-48	48	SM21	20	0.53	0.71	1.7	2.9	5.2	0.43	0.84	1.12	63.4
ICON_020/180-72	72	SM22	20	0.80	1.07	1.9	3.8	7.6	0.61	1.32	1.78	60.2
ICON_020/180-144	144	SM23	20	1.48	1.98	3.1	5.2	15.5	0.67	2.37	3.18	62.3
ICON_030/360-12	12	SM21	80	0.53	0.71	1.7	2.9	5.2	0.43	0.84	1.12	63.4
ICON_030/360-18	18	SM32	40	0.51	0.68	1.9	2.5	5.5	0.39	0.84	1.12	61.0
ICON_030/360-24	24	SM21	40	0.53	0.71	1.7	2.9	5.2	0.43	0.84	1.12	63.4
ICON_030/360-48	48	SM30	20	1.12	1.50	3.6	6.2	11.9	0.43	1.77	2.37	63.1
ICON_030/360-72	72	SM23	40	1.48	1.98	3.1	5.2	15.5	0.67	2.37	3.18	62.3
ICON_030/360-144	144	SM31	20	3.40	4.56	5.2	10.9	33.1	0.68	4.04	5.42	84.2
ICON_040/720-12	12	SM30	80	1.12	1.50	3.6	6.2	11.9	0.43	1.77	2.37	63.1
ICON_040/720-18	18	SM44	40	0.84	1.12	2.6	4.5	7.9	0.39	1.16	1.55	72.4
ICON_040/720-24	24	SM30	40	1.12	1.50	3.6	6.2	11.9	0.43	1.77	2.37	63.1
ICON_040/720-36	36	SM40	40	1.67	2.24	3.6	7.4	18.6	0.67	2.76	3.69	60.6
ICON_040/720-48	48	SM41	20	1.93	2.59	4.4	9.2	16.4	0.49	2.46	3.30	78.5
ICON_040/720-72	72	SM31	40	3.40	4.56	5.2	10.9	33.1	0.68	4.04	5.42	84.2
ICON_040/720-144	144	SM42	20	5.84	7.83	9.3	19.2	51.5	0.73	7.76	10.40	75.3
ICON_050/1440-12	12	SM41	80	1.93	2.59	4.4	9.2	16.4	0.49	2.46	3.30	78.5
ICON_050/1440-18	18	SM40	80	1.67	2.24	3.6	7.4	18.6	0.67	2.76	3.69	60.6
ICON_050/1440-24	24	SM41	40	1.93	2.59	4.4	9.2	16.4	0.49	2.46	3.30	78.5
ICON_050/1440-36	36	SM43	40	2.89	3.87	5.4	10.9	27.0	0.56	3.46	4.63	83.6
ICON_050/1440-48	48	SM50	20	3.88	5.20	6.6	12.3	41.5	0.61	4.60	6.17	84.3
ICON_050/1440-72	72	SM42	40	5.84	7.83	9.3	19.2	51.5	0.73	7.76	10.40	75.3
ICON_050/1440-144	144	SM51	20	11.66	15.62	16.3	36.4	118.5	0.71	13.23	17.73	88.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 10. 3-PH 690 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	SM00	40	0.03	0.03	0.2	0.3	0.4	0.46	0.11	0.15	23.1
ICON_010/30-18	18	SM01	40	0.05	0.07	0.3	0.3	0.5	0.42	0.15	0.20	35.4
ICON_010/30-24	24	SM10	20	0.07	0.10	0.8	1.0	1.5	0.43	0.41	0.55	17.3
ICON_010/30-36	36	SM03	20	0.07	0.10	0.43	0.52	0.81	0.46	0.24	0.32	31.0
ICON_010/30-48	48	SM04	20	0.15	0.20	0.8	1.4	1.7	0.47	0.45	0.60	33.8
ICON_010/30-72	72	SM05	20	0.22	0.29	0.7	1.5	2.7	0.56	0.47	0.63	46.3
ICON_010/30-144	144	SM06	20	0.43	0.58	1.0	1.5	3.8	0.71	0.85	1.14	50.7
ICON_010/90-12	12	SM10	40	0.07	0.10	0.8	1.0	1.5	0.43	0.41	0.55	17.3
ICON_010/90-18	18	SM11	40	0.11	0.14	0.8	0.9	1.7	0.43	0.41	0.55	25.9
ICON_010/90-24	24	SM12	20	0.12	0.16	1.1	1.2	1.7	0.46	0.60	0.81	20.3
ICON_010/90-36	36	SM13	20	0.19	0.26	1.2	1.5	2.2	0.41	0.59	0.79	32.9
ICON_010/90-48	48	SM14	20	0.29	0.39	1.0	1.2	3.2	0.46	0.55	0.74	53.0
ICON_010/90-72	72	SM15	20	0.36	0.49	1.2	1.7	4.6	0.55	0.79	1.06	45.9
ICON_010/90-144	144	SM16	20	0.73	0.98	1.6	2.8	7.9	0.67	1.28	1.72	57.0
ICON_020/180-18	18	SM13	40	0.19	0.26	1.2	1.5	2.2	0.41	0.59	0.79	32.9
ICON_020/180-24	24	SM14	40	0.29	0.39	1.0	1.2	3.2	0.46	0.55	0.74	53.0
ICON_020/180-36	36	SM15	40	0.36	0.49	1.2	1.7	4.6	0.55	0.79	1.06	45.9
ICON_020/180-48	48	SM21	20	0.52	0.70	1.6	2.8	4.9	0.43	0.82	1.10	63.4
ICON_020/180-72	72	SM22	20	0.79	1.06	1.8	3.6	7.3	0.61	1.31	1.76	60.2
ICON_020/180-144	144	SM23	20	1.49	2.00	3.0	4.9	14.8	0.67	2.40	3.22	62.0
ICON_030/360-12	12	SM21	80	0.52	0.70	1.6	2.8	4.9	0.43	0.82	1.10	63.4
ICON_030/360-18	18	SM32	40	0.51	0.68	1.8	2.4	5.3	0.39	0.83	1.11	61.0
ICON_030/360-24	24	SM21	40	0.52	0.70	1.6	2.8	4.9	0.43	0.82	1.10	63.4
ICON_030/360-48	48	SM30	20	1.13	1.52	3.5	6.0	11.4	0.43	1.80	2.41	63.1
ICON_030/360-72	72	SM23	40	1.49	2.00	3.0	4.9	14.8	0.67	2.40	3.22	62.0
ICON_030/360-144	144	SM31	20	3.35	4.49	4.9	10.4	31.7	0.68	3.98	5.34	84.2
ICON_040/720-12	12	SM30	80	1.13	1.52	3.5	6.0	11.4	0.43	1.80	2.41	63.1
ICON_040/720-18	18	SM44	40	0.85	1.14	2.5	4.3	7.5	0.39	1.16	1.56	73.0
ICON_040/720-24	24	SM30	40	1.13	1.52	3.5	6.0	11.4	0.43	1.80	2.41	63.1
ICON_040/720-36	36	SM40	40	1.70	2.28	3.5	7.1	17.7	0.67	2.80	3.76	60.6
ICON_040/720-48	48	SM41	20	1.93	2.59	4.2	8.8	15.7	0.49	2.46	3.30	78.5
ICON_040/720-72	72	SM31	40	3.35	4.49	4.9	10.4	31.7	0.68	3.98	5.34	84.2
ICON_040/720-144	144	SM42	20	5.85	7.83	8.9	18.4	49.3	0.73	7.76	10.40	75.3
ICON_050/1440-12	12	SM41	80	1.93	2.59	4.2	8.8	15.7	0.49	2.46	3.30	78.5
ICON_050/1440-18	18	SM40	80	1.70	2.28	3.5	7.1	17.7	0.67	2.80	3.76	60.6
ICON_050/1440-24	24	SM41	40	1.93	2.59	4.2	8.8	15.7	0.49	2.46	3.30	78.5
ICON_050/1440-36	36	SM43	40	2.91	3.90	5.2	10.4	25.8	0.56	3.48	4.66	83.6
ICON_050/1440-48	48	SM50	20	3.87	5.19	6.3	11.8	39.7	0.61	4.59	6.15	84.3
ICON_050/1440-72	72	SM42	40	5.85	7.83	8.9	18.4	49.3	0.73	7.76	10.40	75.3
ICON_050/1440-144	144	SM51	20	11.66	15.63	15.6	34.8	113.3	0.71	13.24	17.74	88.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 11. 3-PH 208 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	SM00	40	0.04	0.05	1.0	1.1	1.6	0.46	0.17	0.22	22.5
ICON_010/30-22	22	SM01	40	0.06	0.07	1.0	1.2	2.1	0.42	0.15	0.20	36.7
ICON_010/30-29	29	SM10	20	0.08	0.11	3.2	3.8	6.5	0.43	0.50	0.66	17.0
ICON_010/30-43	43	SM03	20	0.09	0.12	1.73	2.08	3.23	0.46	0.46	0.29	31.0
ICON_010/30-58	58	SM04	20	0.17	0.23	3.0	5.4	7.5	0.47	0.51	0.68	34.0
ICON_010/30-86	86	SM05	20	0.26	0.35	2.8	5.9	11.7	0.56	0.56	0.76	46.4
ICON_010/30-173	173	SM06	20	0.51	0.68	3.9	5.7	16.2	0.71	1.00	1.34	51.1
ICON_010/90-14	14	SM10	40	0.08	0.11	3.2	3.8	6.5	0.43	0.50	0.66	17.0
ICON_010/90-22	22	SM11	40	0.13	0.17	3.2	3.6	7.5	0.43	0.50	0.66	25.6
ICON_010/90-29	29	SM12	20	0.15	0.20	4.4	4.8	7.5	0.46	0.73	0.98	20.4
ICON_010/90-43	43	SM13	20	0.22	0.29	4.6	5.9	9.5	0.41	0.68	0.91	32.4
ICON_010/90-58	58	SM14	20	0.34	0.46	3.9	4.8	13.7	0.46	0.65	0.87	52.8
ICON_010/90-86	86	SM15	20	0.45	0.60	4.9	6.8	19.9	0.55	0.97	1.30	45.9
ICON_010/90-173	173	SM16	20	0.89	1.20	6.5	10.9	33.9	0.67	1.57	2.10	56.9
ICON_020/180-22	22	SM13	40	0.22	0.29	4.6	5.9	9.5	0.41	0.68	0.91	32.4
ICON_020/180-29	29	SM14	40	0.34	0.46	3.9	4.8	13.7	0.46	0.65	0.87	52.8
ICON_020/180-43	43	SM15	40	0.45	0.60	4.9	6.8	19.9	0.55	0.97	1.30	45.9
ICON_020/180-58	58	SM21	20	0.64	0.85	6.5	10.9	21.2	0.43	1.01	1.35	63.1
ICON_020/180-86	86	SM22	20	0.95	1.28	7.2	14.0	31.4	0.61	1.58	2.12	60.3
ICON_020/180-173	173	SM23	20	1.77	2.37	11.8	19.2	63.6	0.67	2.85	3.82	62.1
ICON_030/360-14	14	SM21	80	0.64	0.85	6.5	10.9	21.2	0.43	1.01	1.35	63.1
ICON_030/360-22	22	SM32	40	0.61	0.81	7.2	9.3	22.7	0.39	1.00	1.34	60.6
ICON_030/360-29	29	SM21	40	0.64	0.85	6.5	10.9	21.2	0.43	1.01	1.35	63.1
ICON_030/360-58	58	SM30	20	1.35	1.81	13.9	23.3	48.9	0.43	2.15	2.89	62.9
ICON_030/360-86	86	SM23	40	1.77	2.37	11.8	19.2	63.6	0.67	2.85	3.82	62.1
ICON_030/360-173	173	SM31	20	4.04	5.42	19.6	40.5	136.1	0.68	4.80	6.43	84.2
ICON_040/720-14	14	SM30	80	1.35	1.81	13.9	23.3	48.9	0.43	2.15	2.89	62.9
ICON_040/720-22	22	SM44	40	1.01	1.35	9.9	16.7	32.4	0.39	1.39	1.86	72.5
ICON_040/720-29	29	SM30	40	1.35	1.81	13.9	23.3	48.9	0.43	2.15	2.89	62.9
ICON_040/720-43	43	SM40	40	2.03	2.72	13.9	27.6	76.3	0.67	3.36	4.50	60.5
ICON_040/720-58	58	SM41	20	2.34	3.13	16.9	34.4	67.3	0.49	2.98	4.00	78.4
ICON_040/720-86	86	SM31	40	4.04	5.42	19.6	40.5	136.1	0.68	4.80	6.43	84.2
ICON_040/720-173	173	SM42	20	6.98	9.36	35.3	71.7	211.9	0.73	9.28	12.44	75.2
ICON_050/1440-14	14	SM41	80	2.34	3.13	16.9	34.4	67.3	0.49	2.98	4.00	78.4
ICON_050/1440-22	22	SM40	80	2.03	2.72	13.9	27.6	76.3	0.67	3.36	4.50	60.5
ICON_050/1440-29	29	SM41	40	2.34	3.13	16.9	34.4	67.3	0.49	2.98	4.00	78.4
ICON_050/1440-43	43	SM43	40	3.46	4.63	20.5	40.5	110.9	0.56	4.14	5.54	83.6
ICON_050/1440-58	58	SM50	20	4.67	6.26	25.2	45.9	170.7	0.61	5.54	7.42	84.3
ICON_050/1440-86	86	SM42	40	6.98	9.36	35.3	71.7	211.9	0.73	9.28	12.44	75.2
ICON_050/1440-173	173	SM51	20	14.04	18.82	62.1	135.9	487.3	0.71	15.88	21.29	88.4

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 12. 3-PH 220 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	SM00	40	0.04	0.05	0.9	1.0	1.5	0.46	0.16	0.21	22.5
ICON_010/30-22	22	SM01	40	0.06	0.08	1.0	1.2	2.0	0.42	0.16	0.21	36.7
ICON_010/30-29	29	SM10	20	0.09	0.12	3.1	3.6	6.1	0.43	0.51	0.68	17.0
ICON_010/30-43	43	SM03	20	0.09	0.12	1.64	1.96	3.05	0.46	0.46	0.29	31.0
ICON_010/30-58	58	SM04	20	0.17	0.23	2.8	5.1	7.1	0.47	0.50	0.67	34.0
ICON_010/30-86	86	SM05	20	0.26	0.34	2.6	5.6	11.1	0.56	0.55	0.74	46.4
ICON_010/30-173	173	SM06	20	0.51	0.69	3.7	5.4	15.3	0.71	1.00	1.34	51.1
ICON_010/90-14	14	SM10	40	0.09	0.12	3.1	3.6	6.1	0.43	0.51	0.68	17.0
ICON_010/90-22	22	SM11	40	0.13	0.17	3.1	3.4	7.1	0.43	0.51	0.68	25.6
ICON_010/90-29	29	SM12	20	0.15	0.20	4.2	4.5	7.1	0.46	0.74	0.99	20.4
ICON_010/90-43	43	SM13	20	0.22	0.30	4.4	5.6	9.0	0.41	0.69	0.92	32.4
ICON_010/90-58	58	SM14	20	0.34	0.46	3.7	4.5	13.0	0.46	0.65	0.87	52.8
ICON_010/90-86	86	SM15	20	0.44	0.59	4.6	6.4	18.9	0.55	0.96	1.29	45.9
ICON_010/90-173	173	SM16	20	0.88	1.18	6.1	10.3	32.1	0.67	1.56	2.09	56.5
ICON_020/180-22	22	SM13	40	0.22	0.30	4.4	5.6	9.0	0.41	0.69	0.92	32.4
ICON_020/180-29	29	SM14	40	0.34	0.46	3.7	4.5	13.0	0.46	0.65	0.87	52.8
ICON_020/180-43	43	SM15	40	0.44	0.59	4.6	6.4	18.9	0.55	0.96	1.29	45.9
ICON_020/180-58	58	SM21	20	0.63	0.85	6.1	10.3	20.0	0.43	1.00	1.34	63.1
ICON_020/180-86	86	SM22	20	0.95	1.28	6.8	13.3	29.7	0.61	1.58	2.12	60.3
ICON_020/180-173	173	SM23	20	1.76	2.36	11.1	18.2	60.1	0.67	2.83	3.80	62.1
ICON_030/360-14	14	SM21	80	0.63	0.85	6.1	10.3	20.0	0.43	1.00	1.34	63.1
ICON_030/360-22	22	SM32	40	0.61	0.81	6.8	8.8	21.4	0.39	1.00	1.34	60.6
ICON_030/360-29	29	SM21	40	0.63	0.85	6.1	10.3	20.0	0.43	1.00	1.34	63.1
ICON_030/360-58	58	SM30	20	1.35	1.81	13.1	22.0	46.2	0.43	2.15	2.88	62.9
ICON_030/360-86	86	SM23	40	1.76	2.36	11.1	18.2	60.1	0.67	2.83	3.80	62.1
ICON_030/360-173	173	SM31	20	4.06	5.44	18.6	38.3	128.7	0.68	4.82	6.46	84.2
ICON_040/720-14	14	SM30	80	1.35	1.81	13.1	22.0	46.2	0.43	2.15	2.88	62.9
ICON_040/720-22	22	SM44	40	1.01	1.36	9.4	15.8	30.6	0.39	1.40	1.87	72.5
ICON_040/720-29	29	SM30	40	1.35	1.81	13.1	22.0	46.2	0.43	2.15	2.88	62.9
ICON_040/720-43	43	SM40	40	2.02	2.71	13.1	26.1	72.1	0.67	3.34	4.48	60.5
ICON_040/720-58	58	SM41	20	2.33	3.12	15.9	32.5	63.6	0.49	2.97	3.98	78.4
ICON_040/720-86	86	SM31	40	4.06	5.44	18.6	38.3	128.7	0.68	4.82	6.46	84.2
ICON_040/720-173	173	SM42	20	6.99	9.36	33.4	67.8	200.3	0.73	9.29	12.45	75.2
ICON_050/1440-14	14	SM41	80	2.33	3.12	15.9	32.5	63.6	0.49	2.97	3.98	78.4
ICON_050/1440-22	22	SM40	80	2.02	2.71	13.1	26.1	72.1	0.67	3.34	4.48	60.5
ICON_050/1440-29	29	SM41	40	2.33	3.12	15.9	32.5	63.6	0.49	2.97	3.98	78.4
ICON_050/1440-43	43	SM43	40	3.46	4.64	19.4	38.3	104.9	0.56	4.14	5.55	83.6
ICON_050/1440-58	58	SM50	20	4.66	6.25	23.8	43.4	161.4	0.61	5.53	7.41	84.3
ICON_050/1440-86	86	SM42	40	6.99	9.36	33.4	67.8	200.3	0.73	9.29	12.45	75.2
ICON_050/1440-173	173	SM51	20	14.04	18.81	58.7	128.5	460.7	0.71	15.88	21.28	88.4

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 13. 3-PH 280 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	SM00	40	0.04	0.05	0.7	0.8	1.2	0.46	0.16	0.21	22.5
ICON_010/30-22	22	SM01	40	0.06	0.08	0.8	0.9	1.6	0.42	0.16	0.22	36.7
ICON_010/30-29	29	SM10	20	0.09	0.11	2.4	2.9	4.8	0.43	0.50	0.67	17.0
ICON_010/30-43	43	SM03	20	0.09	0.12	1.29	1.54	2.4	0.46	0.46	0.29	31.0
ICON_010/30-58	58	SM04	20	0.17	0.23	2.2	4.0	5.6	0.47	0.50	0.67	34.0
ICON_010/30-86	86	SM05	20	0.26	0.35	2.1	4.4	8.7	0.56	0.57	0.76	46.4
ICON_010/30-173	173	SM06	20	0.51	0.68	2.9	4.2	12.0	0.71	1.00	1.34	51.1
ICON_010/90-14	14	SM10	40	0.09	0.11	2.4	2.9	4.8	0.43	0.50	0.67	17.0
ICON_010/90-22	22	SM11	40	0.13	0.17	2.4	2.7	5.6	0.43	0.50	0.67	25.6
ICON_010/90-29	29	SM12	20	0.15	0.20	3.3	3.5	5.6	0.46	0.74	0.99	20.4
ICON_010/90-43	43	SM13	20	0.22	0.29	3.4	4.4	7.0	0.41	0.68	0.91	32.4
ICON_010/90-58	58	SM14	20	0.35	0.46	2.9	3.5	10.2	0.46	0.65	0.87	53.6
ICON_010/90-86	86	SM15	20	0.44	0.59	3.6	5.0	14.8	0.55	0.96	1.29	45.9
ICON_010/90-173	173	SM16	20	0.88	1.18	4.8	8.1	25.2	0.67	1.56	2.09	56.5
ICON_020/180-22	22	SM13	40	0.22	0.29	3.4	4.4	7.0	0.41	0.68	0.91	32.4
ICON_020/180-29	29	SM14	40	0.35	0.46	2.9	3.5	10.2	0.46	0.65	0.87	53.6
ICON_020/180-43	43	SM15	40	0.44	0.59	3.6	5.0	14.8	0.55	0.96	1.29	45.9
ICON_020/180-58	58	SM21	20	0.63	0.85	4.8	8.1	15.7	0.43	1.00	1.34	63.1
ICON_020/180-86	86	SM22	20	0.95	1.27	5.3	10.4	23.3	0.61	1.57	2.10	60.3
ICON_020/180-173	173	SM23	20	1.76	2.35	8.7	14.3	47.2	0.67	2.83	3.79	62.1
ICON_030/360-14	14	SM21	80	0.63	0.85	4.8	8.1	15.7	0.43	1.00	1.34	63.1
ICON_030/360-22	22	SM32	40	0.60	0.80	5.3	6.9	16.9	0.39	0.99	1.33	60.6
ICON_030/360-29	29	SM21	40	0.63	0.85	4.8	8.1	15.7	0.43	1.00	1.34	63.1
ICON_030/360-58	58	SM30	20	1.35	1.81	10.3	17.3	36.3	0.43	2.15	2.88	62.9
ICON_030/360-86	86	SM23	40	1.76	2.35	8.7	14.3	47.2	0.67	2.83	3.79	62.1
ICON_030/360-173	173	SM31	20	4.05	5.43	14.6	30.1	101.1	0.68	4.81	6.45	84.2
ICON_040/720-14	14	SM30	80	1.35	1.81	10.3	17.3	36.3	0.43	2.15	2.88	62.9
ICON_040/720-22	22	SM44	40	1.01	1.36	7.4	12.4	24.1	0.39	1.40	1.87	72.5
ICON_040/720-29	29	SM30	40	1.35	1.81	10.3	17.3	36.3	0.43	2.15	2.88	62.9
ICON_040/720-43	43	SM40	40	2.02	2.71	10.3	20.5	56.7	0.67	3.35	4.48	60.5
ICON_040/720-58	58	SM41	20	2.33	3.12	12.5	25.5	50.0	0.49	2.97	3.98	78.4
ICON_040/720-86	86	SM31	40	4.05	5.43	14.6	30.1	101.1	0.68	4.81	6.45	84.2
ICON_040/720-173	173	SM42	20	6.98	9.35	26.2	53.3	157.4	0.73	9.28	12.43	75.2
ICON_050/1440-14	14	SM41	80	2.33	3.12	12.5	25.5	50.0	0.49	2.97	3.98	78.4
ICON_050/1440-22	22	SM40	80	2.02	2.71	10.3	20.5	56.7	0.67	3.35	4.48	60.5
ICON_050/1440-29	29	SM41	40	2.33	3.12	12.5	25.5	50.0	0.49	2.97	3.98	78.4
ICON_050/1440-43	43	SM43	40	3.47	4.65	15.3	30.1	82.4	0.56	4.16	5.57	83.6
ICON_050/1440-58	58	SM50	20	4.66	6.25	18.7	34.1	126.8	0.61	5.53	7.41	84.3
ICON_050/1440-86	86	SM42	40	6.98	9.35	26.2	53.3	157.4	0.73	9.28	12.43	75.2
ICON_050/1440-173	173	SM51	20	14.03	18.80	46.1	101.0	362.0	0.71	15.87	21.27	88.4

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 14. 3-PH 380 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	SM00	40	0.03	0.05	0.5	0.6	0.9	0.46	0.15	0.20	22.5
ICON_010/30-22	22	SM01	40	0.06	0.08	0.6	0.7	1.2	0.42	0.17	0.22	36.7
ICON_010/30-29	29	SM10	20	0.09	0.12	1.8	2.1	3.6	0.43	0.51	0.68	17.0
ICON_010/30-43	43	SM03	20	0.09	0.12	0.95	1.14	1.77	0.46	0.46	0.29	31.0
ICON_010/30-58	58	SM04	20	0.17	0.23	1.6	3.0	4.1	0.47	0.49	0.66	34.0
ICON_010/30-86	86	SM05	20	0.25	0.34	1.5	3.2	6.4	0.56	0.55	0.74	45.5
ICON_010/30-173	173	SM06	20	0.53	0.70	2.2	3.1	8.9	0.71	1.03	1.38	51.1
ICON_010/90-14	14	SM10	40	0.09	0.12	1.8	2.1	3.6	0.43	0.51	0.68	17.0
ICON_010/90-22	22	SM11	40	0.13	0.17	1.8	2.0	4.1	0.43	0.51	0.68	25.6
ICON_010/90-29	29	SM12	20	0.15	0.20	2.4	2.6	4.1	0.46	0.73	0.97	20.4
ICON_010/90-43	43	SM13	20	0.22	0.29	2.5	3.2	5.2	0.41	0.67	0.90	32.4
ICON_010/90-58	58	SM14	20	0.35	0.47	2.2	2.6	7.5	0.46	0.67	0.89	52.8
ICON_010/90-86	86	SM15	20	0.45	0.61	2.7	3.7	10.9	0.55	0.98	1.31	46.4
ICON_010/90-173	173	SM16	20	0.87	1.17	3.5	5.9	18.6	0.67	1.54	2.07	56.5
ICON_020/180-22	22	SM13	40	0.22	0.29	2.5	3.2	5.2	0.41	0.67	0.90	32.4
ICON_020/180-29	29	SM14	40	0.35	0.47	2.2	2.6	7.5	0.46	0.67	0.89	52.8
ICON_020/180-43	43	SM15	40	0.45	0.61	2.7	3.7	10.9	0.55	0.98	1.31	46.4
ICON_020/180-58	58	SM21	20	0.63	0.84	3.5	5.9	11.6	0.43	0.99	1.33	63.1
ICON_020/180-86	86	SM22	20	0.94	1.27	3.9	7.7	17.2	0.61	1.57	2.10	60.3
ICON_020/180-173	173	SM23	20	1.75	2.35	6.4	10.5	34.8	0.67	2.82	3.78	62.1
ICON_030/360-14	14	SM21	80	0.63	0.84	3.5	5.9	11.6	0.43	0.99	1.33	63.1
ICON_030/360-22	22	SM32	40	0.60	0.80	3.9	5.1	12.4	0.39	0.99	1.33	60.6
ICON_030/360-29	29	SM21	40	0.63	0.84	3.5	5.9	11.6	0.43	0.99	1.33	63.1
ICON_030/360-58	58	SM30	20	1.35	1.81	7.6	12.8	26.7	0.43	2.15	2.88	62.9
ICON_030/360-86	86	SM23	40	1.75	2.35	6.4	10.5	34.8	0.67	2.82	3.78	62.1
ICON_030/360-173	173	SM31	20	4.03	5.40	10.7	22.2	74.5	0.68	4.79	6.42	84.2
ICON_040/720-14	14	SM30	80	1.35	1.81	7.6	12.8	26.7	0.43	2.15	2.88	62.9
ICON_040/720-22	22	SM44	40	1.00	1.34	5.4	9.2	17.7	0.39	1.38	1.86	72.5
ICON_040/720-29	29	SM30	40	1.35	1.81	7.6	12.8	26.7	0.43	2.15	2.88	62.9
ICON_040/720-43	43	SM40	40	2.03	2.72	7.6	15.1	41.7	0.67	3.35	4.49	60.5
ICON_040/720-58	58	SM41	20	2.33	3.12	9.2	18.8	36.8	0.49	2.97	3.98	78.4
ICON_040/720-86	86	SM31	40	4.03	5.40	10.7	22.2	74.5	0.68	4.79	6.42	84.2
ICON_040/720-173	173	SM42	20	6.97	9.34	19.3	39.2	116.0	0.73	9.27	12.43	75.2
ICON_050/1440-14	14	SM41	80	2.33	3.12	9.2	18.8	36.8	0.49	2.97	3.98	78.4
ICON_050/1440-22	22	SM40	80	2.03	2.72	7.6	15.1	41.7	0.67	3.35	4.49	60.5
ICON_050/1440-29	29	SM41	40	2.33	3.12	9.2	18.8	36.8	0.49	2.97	3.98	78.4
ICON_050/1440-43	43	SM43	40	3.45	4.62	11.2	22.2	60.7	0.56	4.13	5.53	83.6
ICON_050/1440-58	58	SM50	20	4.67	6.26	13.8	25.1	93.5	0.61	5.54	7.42	84.3
ICON_050/1440-86	86	SM42	40	6.97	9.34	19.3	39.2	116.0	0.73	9.27	12.43	75.2
ICON_050/1440-173	173	SM51	20	14.05	18.82	34.0	74.4	266.7	0.71	15.89	21.29	88.4

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 15. 3-PH 400 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	SM00	40	0.04	0.05	0.5	0.6	0.8	0.46	0.16	0.21	24.0
ICON_010/30-22	22	SM01	40	0.05	0.07	0.5	0.7	1.1	0.42	0.15	0.19	36.7
ICON_010/30-29	29	SM10	20	0.09	0.12	1.7	2.0	3.4	0.43	0.51	0.68	17.0
ICON_010/30-43	43	SM03	20	0.09	0.12	0.9	1.08	1.68	0.46	0.46	0.29	31.0
ICON_010/30-58	58	SM04	20	0.18	0.24	1.6	2.8	3.9	0.47	0.52	0.70	34.0
ICON_010/30-86	86	SM05	20	0.25	0.34	1.4	3.1	6.1	0.56	0.54	0.73	46.4
ICON_010/30-173	173	SM06	20	0.50	0.67	2.0	2.9	8.4	0.71	0.98	1.32	51.1
ICON_010/90-14	14	SM10	40	0.09	0.12	1.7	2.0	3.4	0.43	0.51	0.68	17.0
ICON_010/90-22	22	SM11	40	0.13	0.17	1.7	1.9	3.9	0.43	0.51	0.68	25.6
ICON_010/90-29	29	SM12	20	0.15	0.20	2.3	2.5	3.9	0.46	0.73	0.98	20.4
ICON_010/90-43	43	SM13	20	0.22	0.30	2.4	3.1	4.9	0.41	0.68	0.91	32.4
ICON_010/90-58	58	SM14	20	0.34	0.45	2.0	2.5	7.1	0.46	0.64	0.85	52.8
ICON_010/90-86	86	SM15	20	0.44	0.59	2.5	3.5	10.4	0.55	0.95	1.28	45.9
ICON_010/90-173	173	SM16	20	0.89	1.19	3.4	5.6	17.6	0.67	1.58	2.11	56.5
ICON_020/180-22	22	SM13	40	0.22	0.30	2.4	3.1	4.9	0.41	0.68	0.91	32.4
ICON_020/180-29	29	SM14	40	0.34	0.45	2.0	2.5	7.1	0.46	0.64	0.85	52.8
ICON_020/180-43	43	SM15	40	0.44	0.59	2.5	3.5	10.4	0.55	0.95	1.28	45.9
ICON_020/180-58	58	SM21	20	0.64	0.86	3.4	5.6	11.0	0.43	1.01	1.36	63.1
ICON_020/180-86	86	SM22	20	0.94	1.26	3.7	7.3	16.3	0.61	1.56	2.10	60.3
ICON_020/180-173	173	SM23	20	1.76	2.36	6.1	10.0	33.1	0.67	2.83	3.79	62.1
ICON_030/360-14	14	SM21	80	0.64	0.86	3.4	5.6	11.0	0.43	1.01	1.36	63.1
ICON_030/360-22	22	SM32	40	0.60	0.80	3.7	4.8	11.8	0.39	0.99	1.32	60.6
ICON_030/360-29	29	SM21	40	0.64	0.86	3.4	5.6	11.0	0.43	1.01	1.36	63.1
ICON_030/360-58	58	SM30	20	1.35	1.81	7.2	12.1	25.4	0.43	2.14	2.87	62.9
ICON_030/360-86	86	SM23	40	1.76	2.36	6.1	10.0	33.1	0.67	2.83	3.79	62.1
ICON_030/360-173	173	SM31	20	4.05	5.42	10.2	21.1	70.8	0.68	4.81	6.44	84.2
ICON_040/720-14	14	SM30	80	1.35	1.81	7.2	12.1	25.4	0.43	2.14	2.87	62.9
ICON_040/720-22	22	SM44	40	1.02	1.36	5.2	8.7	16.9	0.39	1.40	1.88	72.5
ICON_040/720-29	29	SM30	40	1.35	1.81	7.2	12.1	25.4	0.43	2.14	2.87	62.9
ICON_040/720-43	43	SM40	40	2.02	2.71	7.2	14.4	39.7	0.67	3.34	4.48	60.5
ICON_040/720-58	58	SM41	20	2.34	3.14	8.8	17.9	35.0	0.49	2.99	4.00	78.4
ICON_040/720-86	86	SM31	40	4.05	5.42	10.2	21.1	70.8	0.68	4.81	6.44	84.2
ICON_040/720-173	173	SM42	20	7.00	9.38	18.4	37.3	110.2	0.73	9.31	12.47	75.2
ICON_050/1440-14	14	SM41	80	2.34	3.14	8.8	17.9	35.0	0.49	2.99	4.00	78.4
ICON_050/1440-22	22	SM40	80	2.02	2.71	7.2	14.4	39.7	0.67	3.34	4.48	60.5
ICON_050/1440-29	29	SM41	40	2.34	3.14	8.8	17.9	35.0	0.49	2.99	4.00	78.4
ICON_050/1440-43	43	SM43	40	3.47	4.65	10.7	21.1	57.7	0.56	4.15	5.56	83.6
ICON_050/1440-58	58	SM50	20	4.67	6.25	13.1	23.9	88.8	0.61	5.54	7.42	84.3
ICON_050/1440-86	86	SM42	40	7.00	9.38	18.4	37.3	110.2	0.73	9.31	12.47	75.2
ICON_050/1440-173	173	SM51	20	14.05	18.82	32.3	70.7	253.4	0.71	15.89	21.29	88.4

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 16. 3-PH 440 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	SM00	40	0.04	0.05	0.5	0.5	0.6	0.46	0.18	0.23	22.5
ICON_010/30-22	22	SM01	40	0.06	0.08	0.5	0.6	0.8	0.42	0.16	0.21	36.7
ICON_010/30-29	29	SM10	20	0.08	0.11	1.5	1.7	2.6	0.43	0.49	0.66	17.0
ICON_010/30-43	43	SM03	20	0.09	0.12	0.82	0.94	1.47	0.46	0.46	0.29	31.0
ICON_010/30-58	58	SM04	20	0.17	0.23	1.4	2.5	3.0	0.47	0.50	0.67	34.0
ICON_010/30-86	86	SM05	20	0.26	0.34	1.3	2.7	4.7	0.56	0.55	0.74	46.4
ICON_010/30-173	173	SM06	20	0.53	0.70	1.9	2.6	6.4	0.71	1.03	1.38	51.1
ICON_010/90-14	14	SM10	40	0.08	0.11	1.5	1.7	2.6	0.43	0.49	0.66	17.0
ICON_010/90-22	22	SM11	40	0.13	0.17	1.5	1.6	3.0	0.43	0.49	0.66	25.6
ICON_010/90-29	29	SM12	20	0.15	0.20	2.1	2.2	3.0	0.46	0.74	0.99	20.4
ICON_010/90-43	43	SM13	20	0.22	0.30	2.2	2.7	3.8	0.41	0.69	0.92	32.4
ICON_010/90-58	58	SM14	20	0.36	0.48	1.9	2.2	5.5	0.46	0.67	0.89	53.6
ICON_010/90-86	86	SM15	20	0.44	0.59	2.3	3.1	7.9	0.55	0.96	1.29	45.9
ICON_010/90-173	173	SM16	20	0.90	1.21	3.1	4.9	13.5	0.67	1.58	2.12	56.9
ICON_020/180-22	22	SM13	40	0.22	0.30	2.2	2.7	3.8	0.41	0.69	0.92	32.4
ICON_020/180-29	29	SM14	40	0.36	0.48	1.9	2.2	5.5	0.46	0.67	0.89	53.6
ICON_020/180-43	43	SM15	40	0.44	0.59	2.3	3.1	7.9	0.55	0.96	1.29	45.9
ICON_020/180-58	58	SM21	20	0.65	0.87	3.1	4.9	8.4	0.43	1.02	1.36	63.7
ICON_020/180-86	86	SM22	20	0.95	1.28	3.4	6.4	12.5	0.61	1.58	2.12	60.3
ICON_020/180-173	173	SM23	20	1.78	2.39	5.6	8.7	25.3	0.67	2.86	3.83	62.3
ICON_030/360-14	14	SM21	80	0.65	0.87	3.1	4.9	8.4	0.43	1.02	1.36	63.7
ICON_030/360-22	22	SM32	40	0.61	0.81	3.4	4.2	9.0	0.39	1.00	1.34	60.6
ICON_030/360-29	29	SM21	40	0.65	0.87	3.1	4.9	8.4	0.43	1.02	1.36	63.7
ICON_030/360-58	58	SM30	20	1.36	1.82	6.6	10.5	19.4	0.43	2.16	2.90	62.9
ICON_030/360-86	86	SM23	40	1.78	2.39	5.6	8.7	25.3	0.67	2.86	3.83	62.3
ICON_030/360-173	173	SM31	20	4.06	5.44	9.3	18.3	54.1	0.68	4.82	6.46	84.2
ICON_040/720-14	14	SM30	80	1.36	1.82	6.6	10.5	19.4	0.43	2.16	2.90	62.9
ICON_040/720-22	22	SM44	40	1.01	1.36	4.7	7.6	12.9	0.39	1.40	1.87	72.5
ICON_040/720-29	29	SM30	40	1.36	1.82	6.6	10.5	19.4	0.43	2.16	2.90	62.9
ICON_040/720-43	43	SM40	40	2.04	2.73	6.6	12.5	30.3	0.67	3.37	4.52	60.5
ICON_040/720-58	58	SM41	20	2.34	3.14	8.0	15.6	26.7	0.49	2.99	4.00	78.4
ICON_040/720-86	86	SM31	40	4.06	5.44	9.3	18.3	54.1	0.68	4.82	6.46	84.2
ICON_040/720-173	173	SM42	20	6.99	9.36	16.7	32.5	84.2	0.73	9.29	12.45	75.2
ICON_050/1440-14	14	SM41	80	2.34	3.14	8.0	15.6	26.7	0.49	2.99	4.00	78.4
ICON_050/1440-22	22	SM40	80	2.04	2.73	6.6	12.5	30.3	0.67	3.37	4.52	60.5
ICON_050/1440-29	29	SM41	40	2.34	3.14	8.0	15.6	26.7	0.49	2.99	4.00	78.4
ICON_050/1440-43	43	SM43	40	3.46	4.64	9.7	18.3	44.1	0.56	4.14	5.55	83.6
ICON_050/1440-58	58	SM50	20	4.66	6.25	11.9	20.8	67.8	0.61	5.53	7.41	84.3
ICON_050/1440-86	86	SM42	40	6.99	9.36	16.7	32.5	84.2	0.73	9.29	12.45	75.2
ICON_050/1440-173	173	SM51	20	14.06	18.84	29.4	61.5	193.6	0.71	15.91	21.32	88.4

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 17. 3-PH 460 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	SM00	40	0.03	0.04	0.4	0.5	0.7	0.46	0.15	0.20	22.5
ICON_010/30-22	22	SM01	40	0.06	0.08	0.5	0.6	0.9	0.42	0.17	0.22	36.7
ICON_010/30-29	29	SM10	20	0.09	0.12	1.5	1.7	2.7	0.43	0.51	0.69	17.0
ICON_010/30-43	43	SM03	20	0.09	0.12	0.78	0.92	1.46	0.46	0.46	0.29	31.0
ICON_010/30-58	58	SM04	20	0.18	0.24	1.4	2.4	3.1	0.47	0.52	0.70	34.0
ICON_010/30-86	86	SM05	20	0.27	0.36	1.3	2.6	4.9	0.56	0.58	0.78	46.4
ICON_010/30-173	173	SM06	20	0.52	0.70	1.8	2.5	6.7	0.71	1.02	1.36	51.1
ICON_010/90-14	14	SM10	40	0.09	0.12	1.5	1.7	2.7	0.43	0.51	0.69	17.0
ICON_010/90-22	22	SM11	40	0.13	0.18	1.5	1.6	3.1	0.43	0.51	0.69	25.6
ICON_010/90-29	29	SM12	20	0.15	0.20	2.0	2.1	3.1	0.46	0.73	0.98	20.4
ICON_010/90-43	43	SM13	20	0.22	0.30	2.1	2.6	3.9	0.41	0.69	0.92	32.4
ICON_010/90-58	58	SM14	20	0.35	0.47	1.8	2.1	5.7	0.46	0.66	0.88	53.6
ICON_010/90-86	86	SM15	20	0.44	0.59	2.2	3.0	8.3	0.55	0.96	1.29	45.9
ICON_010/90-173	173	SM16	20	0.88	1.18	2.9	4.8	14.1	0.67	1.55	2.07	56.9
ICON_020/180-22	22	SM13	40	0.22	0.30	2.1	2.6	3.9	0.41	0.69	0.92	32.4
ICON_020/180-29	29	SM14	40	0.35	0.47	1.8	2.1	5.7	0.46	0.66	0.88	53.6
ICON_020/180-43	43	SM15	40	0.44	0.59	2.2	3.0	8.3	0.55	0.96	1.29	45.9
ICON_020/180-58	58	SM21	20	0.63	0.84	2.9	4.8	8.8	0.43	0.99	1.33	63.1
ICON_020/180-86	86	SM22	20	0.94	1.26	3.2	6.2	13.0	0.61	1.56	2.08	60.3
ICON_020/180-173	173	SM23	20	1.76	2.35	5.3	8.5	26.4	0.67	2.83	3.79	62.1
ICON_030/360-14	14	SM21	80	0.63	0.84	2.9	4.8	8.8	0.43	0.99	1.33	63.1
ICON_030/360-22	22	SM32	40	0.60	0.80	3.2	4.1	9.4	0.39	0.98	1.32	60.6
ICON_030/360-29	29	SM21	40	0.63	0.84	2.9	4.8	8.8	0.43	0.99	1.33	63.1
ICON_030/360-58	58	SM30	20	1.36	1.82	6.3	10.3	20.3	0.43	2.16	2.89	62.9
ICON_030/360-86	86	SM23	40	1.76	2.35	5.3	8.5	26.4	0.67	2.83	3.79	62.1
ICON_030/360-173	173	SM31	20	4.06	5.44	8.9	17.9	56.5	0.68	4.82	6.46	84.2
ICON_040/720-14	14	SM30	80	1.36	1.82	6.3	10.3	20.3	0.43	2.16	2.89	62.9
ICON_040/720-22	22	SM44	40	1.01	1.36	4.5	7.4	13.5	0.39	1.40	1.87	72.5
ICON_040/720-29	29	SM30	40	1.36	1.82	6.3	10.3	20.3	0.43	2.16	2.89	62.9
ICON_040/720-43	43	SM40	40	2.03	2.73	6.3	12.2	31.7	0.67	3.36	4.51	60.5
ICON_040/720-58	58	SM41	20	2.33	3.12	7.6	15.2	28.0	0.49	2.97	3.98	78.4
ICON_040/720-86	86	SM31	40	4.06	5.44	8.9	17.9	56.5	0.68	4.82	6.46	84.2
ICON_040/720-173	173	SM42	20	7.00	9.38	16.0	31.7	88.0	0.73	9.31	12.47	75.2
ICON_050/1440-14	14	SM41	80	2.33	3.12	7.6	15.2	28.0	0.49	2.97	3.98	78.4
ICON_050/1440-22	22	SM40	80	2.03	2.73	6.3	12.2	31.7	0.67	3.36	4.51	60.5
ICON_050/1440-29	29	SM41	40	2.33	3.12	7.6	15.2	28.0	0.49	2.97	3.98	78.4
ICON_050/1440-43	43	SM43	40	3.47	4.65	9.3	17.9	46.1	0.56	4.15	5.56	83.6
ICON_050/1440-58	58	SM50	20	4.67	6.26	11.4	20.3	70.9	0.61	5.54	7.42	84.3
ICON_050/1440-86	86	SM42	40	7.00	9.38	16.0	31.7	88.0	0.73	9.31	12.47	75.2
ICON_050/1440-173	173	SM51	20	14.05	18.83	28.1	60.2	202.3	0.71	15.90	21.30	88.4

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 18. 3-PH 480 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	SM00	40	0.03	0.05	0.4	0.5	0.7	0.46	0.15	0.20	22.5
ICON_010/30-22	22	SM01	40	0.05	0.07	0.4	0.5	0.9	0.42	0.14	0.19	36.7
ICON_010/30-29	29	SM10	20	0.09	0.11	1.4	1.7	2.8	0.43	0.50	0.67	17.0
ICON_010/30-43	43	SM03	20	0.09	0.12	0.75	0.9	1.4	0.46	0.29	0.39	31.0
ICON_010/30-58	58	SM04	20	0.17	0.23	1.3	2.4	3.2	0.47	0.51	0.68	34.0
ICON_010/30-86	86	SM05	20	0.26	0.35	1.2	2.6	5.1	0.56	0.56	0.75	46.4
ICON_010/30-173	173	SM06	20	0.51	0.69	1.7	2.5	7.0	0.71	1.00	1.34	51.1
ICON_010/90-14	14	SM10	40	0.09	0.11	1.4	1.7	2.8	0.43	0.50	0.67	17.0
ICON_010/90-22	22	SM11	40	0.13	0.17	1.4	1.6	3.2	0.43	0.50	0.67	25.6
ICON_010/90-29	29	SM12	20	0.15	0.20	1.9	2.1	3.2	0.46	0.73	0.97	20.4
ICON_010/90-43	43	SM13	20	0.22	0.30	2.0	2.6	4.1	0.41	0.68	0.91	32.4
ICON_010/90-58	58	SM14	20	0.34	0.46	1.7	2.1	5.9	0.46	0.65	0.87	52.8
ICON_010/90-86	86	SM15	20	0.44	0.59	2.1	2.9	8.6	0.55	0.96	1.29	45.9
ICON_010/90-173	173	SM16	20	0.88	1.18	2.8	4.7	14.7	0.67	1.56	2.09	56.5
ICON_020/180-22	22	SM13	40	0.22	0.30	2.0	2.6	4.1	0.41	0.68	0.91	32.4
ICON_020/180-29	29	SM14	40	0.34	0.46	1.7	2.1	5.9	0.46	0.65	0.87	52.8
ICON_020/180-43	43	SM15	40	0.44	0.59	2.1	2.9	8.6	0.55	0.96	1.29	45.9
ICON_020/180-58	58	SM21	20	0.63	0.85	2.8	4.7	9.2	0.43	1.00	1.34	63.1
ICON_020/180-86	86	SM22	20	0.95	1.27	3.1	6.1	13.6	0.61	1.57	2.11	60.3
ICON_020/180-173	173	SM23	20	1.76	2.36	5.1	8.3	27.5	0.67	2.84	3.81	62.1
ICON_030/360-14	14	SM21	80	0.63	0.85	2.8	4.7	9.2	0.43	1.00	1.34	63.1
ICON_030/360-22	22	SM32	40	0.60	0.81	3.1	4.0	9.8	0.39	0.99	1.33	60.6
ICON_030/360-29	29	SM21	40	0.63	0.85	2.8	4.7	9.2	0.43	1.00	1.34	63.1
ICON_030/360-58	58	SM30	20	1.35	1.81	6.0	10.1	21.2	0.43	2.14	2.87	62.9
ICON_030/360-86	86	SM23	40	1.76	2.36	5.1	8.3	27.5	0.67	2.84	3.81	62.1
ICON_030/360-173	173	SM31	20	4.05	5.42	8.5	17.5	59.0	0.68	4.81	6.44	84.2
ICON_040/720-14	14	SM30	80	1.35	1.81	6.0	10.1	21.2	0.43	2.14	2.87	62.9
ICON_040/720-22	22	SM44	40	1.01	1.35	4.3	7.3	14.0	0.39	1.39	1.87	72.5
ICON_040/720-29	29	SM30	40	1.35	1.81	6.0	10.1	21.2	0.43	2.14	2.87	62.9
ICON_040/720-43	43	SM40	40	2.02	2.71	6.0	12.0	33.1	0.67	3.34	4.48	60.5
ICON_040/720-58	58	SM41	20	2.33	3.12	7.3	14.9	29.2	0.49	2.97	3.98	78.4
ICON_040/720-86	86	SM31	40	4.05	5.42	8.5	17.5	59.0	0.68	4.81	6.44	84.2
ICON_040/720-173	173	SM42	20	6.98	9.36	15.3	31.1	91.8	0.73	9.29	12.44	75.2
ICON_050/1440-14	14	SM41	80	2.33	3.12	7.3	14.9	29.2	0.49	2.97	3.98	78.4
ICON_050/1440-22	22	SM40	80	2.02	2.71	6.0	12.0	33.1	0.67	3.34	4.48	60.5
ICON_050/1440-29	29	SM41	40	2.33	3.12	7.3	14.9	29.2	0.49	2.97	3.98	78.4
ICON_050/1440-43	43	SM43	40	3.46	4.64	8.9	17.5	48.1	0.56	4.14	5.55	83.6
ICON_050/1440-58	58	SM50	20	4.66	6.24	10.9	19.9	74.0	0.61	5.53	7.41	84.3
ICON_050/1440-86	86	SM42	40	6.98	9.36	15.3	31.1	91.8	0.73	9.29	12.44	75.2
ICON_050/1440-173	173	SM51	20	14.04	18.81	26.9	58.9	211.1	0.71	15.88	21.28	88.4

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 19. 3-PH 575 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	SM00	40	0.04	0.06	0.4	0.4	0.6	0.46	0.18	0.25	22.5
ICON_010/30-22	22	SM01	40	0.06	0.08	0.4	0.5	0.8	0.42	0.17	0.22	36.7
ICON_010/30-29	29	SM10	20	0.09	0.12	1.2	1.4	2.3	0.43	0.51	0.69	17.0
ICON_010/30-43	43	SM03	20	0.09	0.12	0.63	0.75	1.17	0.46	0.46	0.29	31.0
ICON_010/30-58	58	SM04	20	0.17	0.23	1.1	2.0	2.7	0.47	0.51	0.69	33.3
ICON_010/30-86	86	SM05	20	0.26	0.35	1.0	2.1	4.2	0.56	0.56	0.75	46.4
ICON_010/30-173	173	SM06	20	0.51	0.68	1.4	2.1	5.9	0.71	0.99	1.33	51.1
ICON_010/90-14	14	SM10	40	0.09	0.12	1.2	1.4	2.3	0.43	0.51	0.69	17.0
ICON_010/90-22	22	SM11	40	0.13	0.18	1.2	1.3	2.7	0.43	0.51	0.69	25.6
ICON_010/90-29	29	SM12	20	0.15	0.20	1.6	1.7	2.7	0.46	0.73	0.98	20.4
ICON_010/90-43	43	SM13	20	0.22	0.30	1.7	2.1	3.4	0.41	0.69	0.93	32.4
ICON_010/90-58	58	SM14	20	0.34	0.45	1.4	1.7	5.0	0.46	0.64	0.86	52.8
ICON_010/90-86	86	SM15	20	0.46	0.61	1.8	2.5	7.2	0.55	0.99	1.32	46.4
ICON_010/90-173	173	SM16	20	0.87	1.16	2.3	3.9	12.3	0.67	1.53	2.06	56.5
ICON_020/180-22	22	SM13	40	0.22	0.30	1.7	2.1	3.4	0.41	0.69	0.93	32.4
ICON_020/180-29	29	SM14	40	0.34	0.45	1.4	1.7	5.0	0.46	0.64	0.86	52.8
ICON_020/180-43	43	SM15	40	0.46	0.61	1.8	2.5	7.2	0.55	0.99	1.32	46.4
ICON_020/180-58	58	SM21	20	0.62	0.83	2.3	3.9	7.7	0.43	0.98	1.32	63.1
ICON_020/180-86	86	SM22	20	0.95	1.28	2.6	5.1	11.4	0.61	1.58	2.12	60.3
ICON_020/180-173	173	SM23	20	1.78	2.39	4.3	7.0	23.0	0.67	2.87	3.84	62.1
ICON_030/360-14	14	SM21	80	0.62	0.83	2.3	3.9	7.7	0.43	0.98	1.32	63.1
ICON_030/360-22	22	SM32	40	0.60	0.81	2.6	3.4	8.2	0.39	1.00	1.34	60.6
ICON_030/360-29	29	SM21	40	0.62	0.83	2.3	3.9	7.7	0.43	0.98	1.32	63.1
ICON_030/360-58	58	SM30	20	1.35	1.80	5.0	8.4	17.7	0.43	2.14	2.87	62.9
ICON_030/360-86	86	SM23	40	1.78	2.39	4.3	7.0	23.0	0.67	2.87	3.84	62.1
ICON_030/360-173	173	SM31	20	4.05	5.43	7.1	14.6	49.2	0.68	4.81	6.44	84.2
ICON_040/720-14	14	SM30	80	1.35	1.80	5.0	8.4	17.7	0.43	2.14	2.87	62.9
ICON_040/720-22	22	SM44	40	1.01	1.36	3.6	6.1	11.7	0.39	1.40	1.87	72.5
ICON_040/720-29	29	SM30	40	1.35	1.80	5.0	8.4	17.7	0.43	2.14	2.87	62.9
ICON_040/720-43	43	SM40	40	2.02	2.70	5.0	10.0	27.6	0.67	3.34	4.47	60.5
ICON_040/720-58	58	SM41	20	2.33	3.13	6.1	12.4	24.3	0.49	2.98	3.99	78.4
ICON_040/720-86	86	SM31	40	4.05	5.43	7.1	14.6	49.2	0.68	4.81	6.44	84.2
ICON_040/720-173	173	SM42	20	7.00	9.38	12.8	25.9	76.6	0.73	9.31	12.47	75.2
ICON_050/1440-14	14	SM41	80	2.33	3.13	6.1	12.4	24.3	0.49	2.98	3.99	78.4
ICON_050/1440-22	22	SM40	80	2.02	2.70	5.0	10.0	27.6	0.67	3.34	4.47	60.5
ICON_050/1440-29	29	SM41	40	2.33	3.13	6.1	12.4	24.3	0.49	2.98	3.99	78.4
ICON_050/1440-43	43	SM43	40	3.45	4.62	7.4	14.6	40.1	0.56	4.13	5.53	83.6
ICON_050/1440-58	58	SM50	20	4.66	6.24	9.1	16.6	61.8	0.61	5.53	7.41	84.3
ICON_050/1440-86	86	SM42	40	7.00	9.38	12.8	25.9	76.6	0.73	9.31	12.47	75.2
ICON_050/1440-173	173	SM51	20	14.06	18.85	22.5	49.2	176.3	0.71	15.91	21.32	88.4

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

**Table 20. Short time duty (S2-30') | Inching Duty (S4-25% -600 St/h)
3-PH 220 V 50 Hz**

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	TM00	40	0.03	0.04	0.8	0.9	1.1	0.46	0.14	0.19	23.1
ICON_010/30-18	18	TM01	40	0.05	0.07	0.8	1.0	1.4	0.42	0.13	0.17	38.3
ICON_010/30-24	24	TM10	20	0.07	0.10	2.6	3.0	4.3	0.43	0.43	0.57	17.3
ICON_010/30-36	36	TM03	20	0.07	0.10	1.36	1.6	2.33	0.46	0.24	0.32	31.0
ICON_010/30-48	48	TM04	20	0.15	0.19	2.4	4.3	5.0	0.47	0.43	0.58	33.8
ICON_010/30-72	72	TM05	20	0.22	0.29	2.2	4.6	7.8	0.56	0.47	0.63	46.3
ICON_010/30-144	144	TM06	20	0.43	0.58	3.1	4.5	10.8	0.71	0.84	1.12	51.3
ICON_010/90-12	12	TM10	40	0.07	0.10	2.6	3.0	4.3	0.43	0.43	0.57	17.3
ICON_010/90-18	18	TM11	40	0.11	0.15	2.6	2.9	5.0	0.43	0.43	0.57	25.9
ICON_010/90-24	24	TM12	20	0.12	0.16	3.5	3.7	5.0	0.46	0.61	0.82	20.0
ICON_010/90-36	36	TM13	20	0.18	0.24	3.6	4.6	6.3	0.41	0.56	0.75	32.1
ICON_010/90-48	48	TM14	20	0.28	0.38	3.1	3.7	9.2	0.46	0.54	0.73	51.9
ICON_010/90-72	72	TM15	20	0.36	0.48	3.8	5.3	13.3	0.55	0.80	1.07	45.0
ICON_010/90-144	144	TM16	20	0.74	0.99	5.1	8.5	22.6	0.67	1.30	1.74	56.6
ICON_020/180-18	18	TM13	40	0.18	0.24	3.6	4.6	6.3	0.41	0.56	0.75	32.1
ICON_020/180-24	24	TM14	40	0.28	0.38	3.1	3.7	9.2	0.46	0.54	0.73	51.9
ICON_020/180-36	36	TM15	40	0.36	0.48	3.8	5.3	13.3	0.55	0.80	1.07	45.0
ICON_020/180-48	48	TM21	20	0.52	0.70	5.1	8.5	14.1	0.43	0.84	1.12	62.7
ICON_020/180-72	72	TM22	20	0.77	1.04	5.6	11.0	21.0	0.61	1.30	1.74	59.5
ICON_020/180-144	144	TM23	20	1.48	1.98	9.3	15.1	42.4	0.67	2.37	3.18	62.3
ICON_030/360-24	24	TM21	40	0.52	0.70	5.1	8.5	14.1	0.43	0.84	1.12	62.7
ICON_030/360-48	48	TM30	20	1.12	1.51	10.9	18.3	32.6	0.43	1.79	2.39	62.9
ICON_030/360-72	72	TM23	40	1.48	1.98	9.3	15.1	42.4	0.67	2.37	3.18	62.3
ICON_030/360-144	144	TM31	20	3.37	4.52	15.5	31.8	90.8	0.68	4.02	5.38	84.0
ICON_040/720-24	24	TM30	40	1.12	1.51	10.9	18.3	32.6	0.43	1.79	2.39	62.9
ICON_040/720-36	36	TM40	40	1.68	2.25	10.9	21.7	50.9	0.67	2.78	3.73	60.4
ICON_040/720-72	72	TM31	40	3.37	4.52	15.5	31.8	90.8	0.68	4.02	5.38	84.0

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 21. 3-PH 230 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	TM00	40	0.03	0.04	0.7	0.8	1.1	0.46	0.13	0.17	22.4
ICON_010/30-18	18	TM01	40	0.05	0.06	0.8	1.0	1.5	0.42	0.13	0.18	35.9
ICON_010/30-24	24	TM10	20	0.07	0.09	2.4	3.0	4.5	0.43	0.41	0.55	17.0
ICON_010/30-36	36	TM03	20	0.07	0.10	1.3	1.56	2.44	0.46	0.24	0.32	31.0
ICON_010/30-48	48	TM04	20	0.14	0.19	2.3	4.2	5.2	0.47	0.43	0.58	33.5
ICON_010/30-72	72	TM05	20	0.21	0.29	2.1	4.5	8.2	0.56	0.47	0.63	45.8
ICON_010/30-144	144	TM06	20	0.43	0.58	3.0	4.4	11.3	0.71	0.85	1.14	50.9
ICON_010/90-12	12	TM10	40	0.07	0.09	2.4	3.0	4.5	0.43	0.41	0.55	17.0
ICON_010/90-18	18	TM11	40	0.10	0.14	2.4	2.8	5.2	0.43	0.41	0.55	25.4
ICON_010/90-24	24	TM12	20	0.12	0.16	3.3	3.7	5.2	0.46	0.60	0.81	20.2
ICON_010/90-36	36	TM13	20	0.19	0.25	3.5	4.5	6.6	0.41	0.57	0.77	32.4
ICON_010/90-48	48	TM14	20	0.29	0.39	3.0	3.7	9.6	0.46	0.55	0.74	52.8
ICON_010/90-72	72	TM15	20	0.37	0.50	3.7	5.2	13.9	0.55	0.81	1.09	45.9
ICON_010/90-144	144	TM16	20	0.74	0.99	4.9	8.4	23.7	0.67	1.31	1.75	56.6
ICON_020/180-18	18	TM13	40	0.19	0.25	3.5	4.5	6.6	0.41	0.57	0.77	32.4
ICON_020/180-24	24	TM14	40	0.29	0.39	3.0	3.7	9.6	0.46	0.55	0.74	52.8
ICON_020/180-36	36	TM15	40	0.37	0.50	3.7	5.2	13.9	0.55	0.81	1.09	45.9
ICON_020/180-48	48	TM21	20	0.53	0.71	4.9	8.4	14.8	0.43	0.84	1.12	63.1
ICON_020/180-72	72	TM22	20	0.79	1.06	5.4	10.8	21.9	0.61	1.31	1.76	60.2
ICON_020/180-144	144	TM23	20	1.48	1.98	8.9	14.8	44.4	0.67	2.38	3.18	62.1
ICON_030/360-24	24	TM21	40	0.53	0.71	4.9	8.4	14.8	0.43	0.84	1.12	63.1
ICON_030/360-48	48	TM30	20	1.12	1.50	10.4	17.9	34.1	0.43	1.78	2.39	62.8
ICON_030/360-72	72	TM23	40	1.48	1.98	8.9	14.8	44.4	0.67	2.38	3.18	62.1
ICON_030/360-144	144	TM31	20	3.37	4.52	14.8	31.1	95.0	0.68	4.01	5.37	84.1
ICON_040/720-24	24	TM30	40	1.12	1.50	10.4	17.9	34.1	0.43	1.78	2.39	62.8
ICON_040/720-36	36	TM40	40	1.68	2.25	10.4	21.2	53.2	0.67	2.78	3.72	60.5
ICON_040/720-72	72	TM31	40	3.37	4.52	14.8	31.1	95.0	0.68	4.01	5.37	84.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 22. 3-PH 240 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	TM00	40	0.03	0.04	0.7	0.8	1.2	0.46	0.13	0.18	23.1
ICON_010/30-18	18	TM01	40	0.05	0.06	0.7	0.9	1.5	0.42	0.12	0.16	38.3
ICON_010/30-24	24	TM10	20	0.07	0.10	2.3	2.9	4.7	0.43	0.41	0.55	17.3
ICON_010/30-36	36	TM03	20	0.07	0.10	1.25	1.53	2.54	0.46	0.24	0.32	31.0
ICON_010/30-48	48	TM04	20	0.15	0.19	2.2	4.1	5.4	0.47	0.43	0.58	33.8
ICON_010/30-72	72	TM05	20	0.22	0.29	2.0	4.4	8.5	0.56	0.47	0.62	46.3
ICON_010/30-144	144	TM06	20	0.42	0.57	2.8	4.3	11.8	0.71	0.83	1.11	51.3
ICON_010/90-12	12	TM10	40	0.07	0.10	2.3	2.9	4.7	0.43	0.41	0.55	17.3
ICON_010/90-18	18	TM11	40	0.11	0.14	2.3	2.7	5.4	0.43	0.41	0.55	25.9
ICON_010/90-24	24	TM12	20	0.12	0.16	3.2	3.6	5.4	0.46	0.61	0.82	20.0
ICON_010/90-36	36	TM13	20	0.18	0.24	3.3	4.4	6.9	0.41	0.56	0.75	32.1
ICON_010/90-48	48	TM14	20	0.28	0.37	2.8	3.6	10.0	0.46	0.54	0.72	51.9
ICON_010/90-72	72	TM15	20	0.36	0.48	3.5	5.1	14.5	0.55	0.80	1.07	45.0
ICON_010/90-144	144	TM16	20	0.74	0.99	4.7	8.2	24.7	0.67	1.31	1.75	56.2
ICON_020/180-18	18	TM13	40	0.18	0.24	3.3	4.4	6.9	0.41	0.56	0.75	32.1
ICON_020/180-24	24	TM14	40	0.28	0.37	2.8	3.6	10.0	0.46	0.54	0.72	51.9
ICON_020/180-36	36	TM15	40	0.36	0.48	3.5	5.1	14.5	0.55	0.80	1.07	45.0
ICON_020/180-48	48	TM21	20	0.53	0.71	4.7	8.2	15.4	0.43	0.84	1.13	62.7
ICON_020/180-72	72	TM22	20	0.78	1.05	5.2	10.6	22.9	0.61	1.32	1.77	59.5
ICON_020/180-144	144	TM23	20	1.47	1.98	8.5	14.5	46.3	0.67	2.37	3.17	62.3
ICON_030/360-24	24	TM21	40	0.53	0.71	4.7	8.2	15.4	0.43	0.84	1.13	62.7
ICON_030/360-48	48	TM30	20	1.12	1.51	10.0	17.5	35.6	0.43	1.79	2.40	62.9
ICON_030/360-72	72	TM23	40	1.47	1.98	8.5	14.5	46.3	0.67	2.37	3.17	62.3
ICON_030/360-144	144	TM31	20	3.37	4.52	14.2	30.5	99.1	0.68	4.01	5.38	84.0
ICON_040/720-24	24	TM30	40	1.12	1.51	10.0	17.5	35.6	0.43	1.79	2.40	62.9
ICON_040/720-36	36	TM40	40	1.68	2.25	10.0	20.8	55.5	0.67	2.79	3.73	60.4
ICON_040/720-72	72	TM31	40	3.37	4.52	14.2	30.5	99.1	0.68	4.01	5.38	84.0

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 23. 3-PH 380 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	TM00	40	0.03	0.04	0.4	0.5	0.6	0.46	0.12	0.16	23.1
ICON_010/30-18	18	TM01	40	0.05	0.07	0.5	0.6	0.8	0.42	0.14	0.19	38.3
ICON_010/30-24	24	TM10	20	0.07	0.10	1.5	1.7	2.5	0.43	0.42	0.57	17.3
ICON_010/30-36	36	TM03	20	0.07	0.10	0.79	0.92	1.48	0.46	0.24	0.32	31.0
ICON_010/30-48	48	TM04	20	0.15	0.20	1.4	2.5	2.9	0.47	0.43	0.58	33.8
ICON_010/30-72	72	TM05	20	0.22	0.30	1.3	2.7	4.5	0.56	0.48	0.64	46.3
ICON_010/30-144	144	TM06	20	0.43	0.58	1.8	2.6	6.2	0.71	0.84	1.13	51.3
ICON_010/90-12	12	TM10	40	0.07	0.10	1.5	1.7	2.5	0.43	0.42	0.57	17.3
ICON_010/90-18	18	TM11	40	0.11	0.15	1.5	1.6	2.9	0.43	0.42	0.57	25.9
ICON_010/90-24	24	TM12	20	0.12	0.16	2.0	2.2	2.9	0.46	0.61	0.81	20.3
ICON_010/90-36	36	TM13	20	0.18	0.24	2.1	2.7	3.6	0.41	0.57	0.76	32.1
ICON_010/90-48	48	TM14	20	0.29	0.39	1.8	2.2	5.2	0.46	0.54	0.73	53.0
ICON_010/90-72	72	TM15	20	0.37	0.49	2.2	3.1	7.6	0.55	0.80	1.07	45.9
ICON_010/90-144	144	TM16	20	0.75	1.00	3.0	4.9	12.9	0.67	1.32	1.77	56.5
ICON_020/180-18	18	TM13	40	0.18	0.24	2.1	2.7	3.6	0.41	0.57	0.76	32.1
ICON_020/180-24	24	TM14	40	0.29	0.39	1.8	2.2	5.2	0.46	0.54	0.73	53.0
ICON_020/180-36	36	TM15	40	0.37	0.49	2.2	3.1	7.6	0.55	0.80	1.07	45.9
ICON_020/180-48	48	TM21	20	0.54	0.72	3.0	4.9	8.1	0.43	0.85	1.14	63.4
ICON_020/180-72	72	TM22	20	0.80	1.08	3.3	6.4	12.0	0.61	1.32	1.78	60.7
ICON_020/180-144	144	TM23	20	1.48	1.99	5.4	8.7	24.2	0.67	2.38	3.19	62.3
ICON_030/360-24	24	TM21	40	0.54	0.72	3.0	4.9	8.1	0.43	0.85	1.14	63.4
ICON_030/360-48	48	TM30	20	1.13	1.51	6.3	10.6	18.6	0.43	1.78	2.39	63.1
ICON_030/360-72	72	TM23	40	1.48	1.99	5.4	8.7	24.2	0.67	2.38	3.19	62.3
ICON_030/360-144	144	TM31	20	3.39	4.54	9.0	18.4	51.9	0.68	4.03	5.40	84.2
ICON_040/720-24	24	TM30	40	1.13	1.51	6.3	10.6	18.6	0.43	1.78	2.39	63.1
ICON_040/720-36	36	TM40	40	1.68	2.26	6.3	12.5	29.1	0.67	2.78	3.72	60.6
ICON_040/720-72	72	TM31	40	3.39	4.54	9.0	18.4	51.9	0.68	4.03	5.40	84.2

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 24. 3-PH 400 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	TM00	40	0.03	0.04	0.4	0.5	0.7	0.46	0.13	0.17	23.1
ICON_010/30-18	18	TM01	40	0.04	0.06	0.4	0.6	0.9	0.42	0.12	0.16	38.3
ICON_010/30-24	24	TM10	20	0.07	0.10	1.4	1.7	2.6	0.43	0.42	0.56	17.3
ICON_010/30-36	36	TM03	20	0.07	0.10	0.75	0.9	1.4	0.46	0.24	0.32	31.0
ICON_010/30-48	48	TM04	20	0.14	0.19	1.3	2.4	3.0	0.47	0.42	0.57	33.8
ICON_010/30-72	72	TM05	20	0.22	0.29	1.2	2.6	4.7	0.56	0.47	0.62	46.3
ICON_010/30-144	144	TM06	20	0.43	0.57	1.7	2.5	6.5	0.71	0.84	1.12	51.3
ICON_010/90-12	12	TM10	40	0.07	0.10	1.4	1.7	2.6	0.43	0.42	0.56	17.3
ICON_010/90-18	18	TM11	40	0.11	0.14	1.4	1.6	3.0	0.43	0.42	0.56	25.9
ICON_010/90-24	24	TM12	20	0.12	0.16	1.9	2.1	3.0	0.46	0.61	0.81	20.3
ICON_010/90-36	36	TM13	20	0.19	0.25	2.0	2.6	3.8	0.41	0.57	0.76	32.9
ICON_010/90-48	48	TM14	20	0.29	0.38	1.7	2.1	5.5	0.46	0.54	0.73	53.0
ICON_010/90-72	72	TM15	20	0.37	0.49	2.1	3.0	8.0	0.55	0.80	1.07	45.9
ICON_010/90-144	144	TM16	20	0.73	0.98	2.8	4.8	13.6	0.67	1.30	1.74	56.5
ICON_020/180-18	18	TM13	40	0.19	0.25	2.0	2.6	3.8	0.41	0.57	0.76	32.9
ICON_020/180-24	24	TM14	40	0.29	0.38	1.7	2.1	5.5	0.46	0.54	0.73	53.0
ICON_020/180-36	36	TM15	40	0.37	0.49	2.1	3.0	8.0	0.55	0.80	1.07	45.9
ICON_020/180-48	48	TM21	20	0.53	0.71	2.8	4.8	8.5	0.43	0.83	1.12	63.4
ICON_020/180-72	72	TM22	20	0.79	1.06	3.1	6.2	12.6	0.61	1.31	1.76	60.2
ICON_020/180-144	144	TM23	20	1.47	1.98	5.1	8.5	25.5	0.67	2.37	3.17	62.3
ICON_030/360-24	24	TM21	40	0.53	0.71	2.8	4.8	8.5	0.43	0.83	1.12	63.4
ICON_030/360-48	48	TM30	20	1.13	1.51	6.0	10.3	19.6	0.43	1.79	2.40	63.1
ICON_030/360-72	72	TM23	40	1.47	1.98	5.1	8.5	25.5	0.67	2.37	3.17	62.3
ICON_030/360-144	144	TM31	20	3.37	4.52	8.5	17.9	54.6	0.68	4.00	5.37	84.2
ICON_040/720-24	24	TM30	40	1.13	1.51	6.0	10.3	19.6	0.43	1.79	2.40	63.1
ICON_040/720-36	36	TM40	40	1.69	2.26	6.0	12.2	30.6	0.67	2.79	3.73	60.6
ICON_040/720-72	72	TM31	40	3.37	4.52	8.5	17.9	54.6	0.68	4.00	5.37	84.2

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 25. 3-PH 415 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	TM00	40	0.03	0.04	0.4	0.5	0.7	0.46	0.13	0.18	23.1
ICON_010/30-18	18	TM01	40	0.05	0.06	0.4	0.5	0.9	0.42	0.12	0.16	38.3
ICON_010/30-24	24	TM10	20	0.07	0.10	1.4	1.7	2.7	0.43	0.43	0.58	17.3
ICON_010/30-36	36	TM03	20	0.07	0.10	0.72	0.89	1.38	0.46	0.24	0.32	31.0
ICON_010/30-48	48	TM04	20	0.15	0.20	1.3	2.4	3.1	0.47	0.44	0.59	33.8
ICON_010/30-72	72	TM05	20	0.22	0.30	1.2	2.6	4.9	0.56	0.48	0.65	46.3
ICON_010/30-144	144	TM06	20	0.42	0.56	1.6	2.5	6.7	0.71	0.82	1.09	51.3
ICON_010/90-12	12	TM10	40	0.07	0.10	1.4	1.7	2.7	0.43	0.43	0.58	17.3
ICON_010/90-18	18	TM11	40	0.11	0.15	1.4	1.6	3.1	0.43	0.43	0.58	25.9
ICON_010/90-24	24	TM12	20	0.12	0.16	1.8	2.1	3.1	0.46	0.60	0.80	20.3
ICON_010/90-36	36	TM13	20	0.18	0.25	1.9	2.6	3.9	0.41	0.56	0.75	32.9
ICON_010/90-48	48	TM14	20	0.28	0.38	1.6	2.1	5.7	0.46	0.53	0.71	53.0
ICON_010/90-72	72	TM15	20	0.37	0.49	2.0	3.0	8.3	0.55	0.79	1.06	46.5
ICON_010/90-144	144	TM16	20	0.73	0.98	2.7	4.7	14.1	0.67	1.30	1.74	56.5
ICON_020/180-18	18	TM13	40	0.18	0.25	1.9	2.6	3.9	0.41	0.56	0.75	32.9
ICON_020/180-24	24	TM14	40	0.28	0.38	1.6	2.1	5.7	0.46	0.53	0.71	53.0
ICON_020/180-36	36	TM15	40	0.37	0.49	2.0	3.0	8.3	0.55	0.79	1.06	46.5
ICON_020/180-48	48	TM21	20	0.53	0.71	2.7	4.7	8.8	0.43	0.83	1.12	63.4
ICON_020/180-72	72	TM22	20	0.79	1.06	3.0	6.1	13.1	0.61	1.32	1.76	60.2
ICON_020/180-144	144	TM23	20	1.47	1.97	4.9	8.3	26.5	0.67	2.36	3.16	62.3
ICON_030/360-24	24	TM21	40	0.53	0.71	2.7	4.7	8.8	0.43	0.83	1.12	63.4
ICON_030/360-48	48	TM30	20	1.13	1.52	5.8	10.1	20.3	0.43	1.79	2.40	63.1
ICON_030/360-72	72	TM23	40	1.47	1.97	4.9	8.3	26.5	0.67	2.36	3.16	62.3
ICON_030/360-144	144	TM31	20	3.37	4.52	8.2	17.6	56.7	0.68	4.01	5.37	84.2
ICON_040/720-24	24	TM30	40	1.13	1.52	5.8	10.1	20.3	0.43	1.79	2.40	63.1
ICON_040/720-36	36	TM40	40	1.69	2.27	5.8	12.0	31.8	0.67	2.79	3.74	60.6
ICON_040/720-72	72	TM31	40	3.37	4.52	8.2	17.6	56.7	0.68	4.01	5.37	84.2

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 26. 3-PH 440 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	TM00	40	0.03	0.04	0.4	0.5	0.7	0.46	0.14	0.19	21.4
ICON_010/30-18	18	TM01	40	0.05	0.06	0.4	0.5	0.9	0.42	0.13	0.17	35.4
ICON_010/30-24	24	TM10	20	0.07	0.10	1.4	1.7	2.7	0.43	0.46	0.61	16.1
ICON_010/30-36	36	TM03	20	0.07	0.10	0.75	0.9	1.4	0.46	0.24	0.32	31.0
ICON_010/30-48	48	TM04	20	0.15	0.20	1.3	2.4	3.1	0.47	0.47	0.62	32.3
ICON_010/30-72	72	TM05	20	0.22	0.30	1.2	2.6	4.9	0.56	0.51	0.69	43.5
ICON_010/30-144	144	TM06	20	0.42	0.56	1.6	2.5	6.7	0.71	0.87	1.16	48.4
ICON_010/90-12	12	TM10	40	0.07	0.10	1.4	1.7	2.7	0.43	0.46	0.61	16.1
ICON_010/90-18	18	TM11	40	0.11	0.15	1.4	1.6	3.1	0.43	0.46	0.61	24.1
ICON_010/90-24	24	TM12	20	0.12	0.16	1.8	2.1	3.1	0.46	0.63	0.85	19.1
ICON_010/90-36	36	TM13	20	0.18	0.24	1.9	2.6	3.9	0.41	0.59	0.80	30.7
ICON_010/90-48	48	TM14	20	0.28	0.38	1.6	2.1	5.7	0.46	0.56	0.75	50.2
ICON_010/90-72	72	TM15	20	0.37	0.49	2.0	3.0	8.3	0.55	0.84	1.12	43.7
ICON_010/90-144	144	TM16	20	0.74	0.99	2.7	4.7	14.1	0.67	1.38	1.85	53.7
ICON_020/180-18	18	TM13	40	0.18	0.24	1.9	2.6	3.9	0.41	0.59	0.80	30.7
ICON_020/180-24	24	TM14	40	0.28	0.38	1.6	2.1	5.7	0.46	0.56	0.75	50.2
ICON_020/180-36	36	TM15	40	0.37	0.49	2.0	3.0	8.3	0.55	0.84	1.12	43.7
ICON_020/180-48	48	TM21	20	0.53	0.71	2.7	4.7	8.8	0.43	0.88	1.19	59.8
ICON_020/180-72	72	TM22	20	0.79	1.06	3.0	6.1	13.1	0.61	1.39	1.87	56.8
ICON_020/180-144	144	TM23	20	1.47	1.96	4.9	8.3	26.5	0.67	2.50	3.35	58.6
ICON_030/360-24	24	TM21	40	0.53	0.71	2.7	4.7	8.8	0.43	0.88	1.19	59.8
ICON_030/360-48	48	TM30	20	1.13	1.51	5.8	10.1	20.3	0.43	1.90	2.55	59.4
ICON_030/360-72	72	TM23	40	1.47	1.96	4.9	8.3	26.5	0.67	2.50	3.35	58.6
ICON_030/360-144	144	TM31	20	3.37	4.52	8.2	17.6	56.7	0.68	4.25	5.69	79.4
ICON_040/720-24	24	TM30	40	1.13	1.51	5.8	10.1	20.3	0.43	1.90	2.55	59.4
ICON_040/720-36	36	TM40	40	1.69	2.27	5.8	12.0	31.8	0.67	2.96	3.97	57.1
ICON_040/720-72	72	TM31	40	3.37	4.52	8.2	17.6	56.7	0.68	4.25	5.69	79.4

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values..

Table 27. 3-PH 660 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-12	12	TM00	40	0.04	0.05	0.3	0.3	0.4	0.46	0.16	0.21	23.1
ICON_010/30-18	18	TM01	40	0.04	0.06	0.3	0.3	0.5	0.42	0.14	0.19	30.8
ICON_010/30-24	24	TM10	20	0.08	0.10	0.9	1.0	1.6	0.43	0.44	0.59	17.1
ICON_010/30-36	36	TM03	20	0.07	0.10	0.46	0.54	0.85	0.46	0.24	0.32	31.0
ICON_010/30-48	48	TM04	20	0.14	0.19	0.8	1.5	1.8	0.47	0.43	0.58	33.3
ICON_010/30-72	72	TM05	20	0.20	0.27	0.7	1.6	2.9	0.56	0.45	0.60	45.7
ICON_010/30-144	144	TM06	20	0.41	0.55	1.0	1.5	3.9	0.71	0.81	1.09	50.6
ICON_010/90-12	12	TM10	40	0.08	0.10	0.9	1.0	1.6	0.43	0.44	0.59	17.1
ICON_010/90-18	18	TM11	40	0.12	0.16	0.9	1.0	1.8	0.43	0.44	0.59	26.8
ICON_010/90-24	24	TM12	20	0.13	0.17	1.2	1.3	1.8	0.46	0.63	0.85	20.0
ICON_010/90-36	36	TM13	20	0.19	0.25	1.2	1.6	2.3	0.41	0.56	0.75	32.9
ICON_010/90-48	48	TM14	20	0.28	0.37	1.0	1.3	3.3	0.46	0.53	0.70	53.0
ICON_010/90-72	72	TM15	20	0.38	0.51	1.3	1.8	4.9	0.55	0.82	1.10	46.5
ICON_010/90-144	144	TM16	20	0.74	0.99	1.7	2.9	8.2	0.67	1.30	1.74	56.5
ICON_020/180-18	18	TM13	40	0.19	0.25	1.2	1.6	2.3	0.41	0.56	0.75	32.9
ICON_020/180-24	24	TM14	40	0.28	0.37	1.0	1.3	3.3	0.46	0.53	0.70	53.0
ICON_020/180-36	36	TM15	40	0.38	0.51	1.3	1.8	4.9	0.55	0.82	1.10	46.5
ICON_020/180-48	48	TM21	20	0.53	0.71	1.7	2.9	5.2	0.43	0.84	1.12	63.4
ICON_020/180-72	72	TM22	20	0.80	1.07	1.9	3.8	7.6	0.61	1.32	1.78	60.2
ICON_020/180-144	144	TM23	20	1.48	1.98	3.1	5.2	15.5	0.67	2.37	3.18	62.3
ICON_030/360-24	24	TM21	40	0.53	0.71	1.7	2.9	5.2	0.43	0.84	1.12	63.4
ICON_030/360-48	48	TM30	20	1.12	1.50	3.6	6.2	11.9	0.43	1.77	2.37	63.1
ICON_030/360-72	72	TM23	40	1.48	1.98	3.1	5.2	15.5	0.67	2.37	3.18	62.3
ICON_030/360-144	144	TM31	20	3.40	4.56	5.2	10.9	33.1	0.68	4.04	5.42	84.2
ICON_040/720-24	24	TM30	40	1.12	1.50	3.6	6.2	11.9	0.43	1.77	2.37	63.1
ICON_040/720-36	36	TM40	40	1.67	2.24	3.6	7.4	18.6	0.67	2.76	3.69	60.6
ICON_040/720-72	72	TM31	40	3.40	4.56	5.2	10.9	33.1	0.68	4.04	5.42	84.2

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 28. 3-PH 280 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	TM00	40	0.04	0.05	0.7	0.8	1.2	0.46	0.16	0.21	22.5
ICON_010/30-22	22	TM01	40	0.06	0.08	0.8	0.9	1.6	0.42	0.16	0.22	36.7
ICON_010/30-29	29	TM10	20	0.08	0.11	2.4	2.9	4.8	0.43	0.50	0.67	16.0
ICON_010/30-43	43	TM03	20	0.09	0.12	1.29	1.54	2.4	0.46	0.46	0.29	31.0
ICON_010/30-58	58	TM04	20	0.17	0.23	2.2	4.0	5.6	0.47	0.50	0.67	34.0
ICON_010/30-86	86	TM05	20	0.27	0.36	2.1	4.4	8.7	0.56	0.57	0.76	46.6
ICON_010/30-173	173	TM06	20	0.51	0.68	2.9	4.2	12.0	0.71	1.00	1.34	51.1
ICON_010/90-14	14	TM10	40	0.08	0.11	2.4	2.9	4.8	0.43	0.50	0.67	16.0
ICON_010/90-22	22	TM11	40	0.12	0.16	2.4	2.7	5.6	0.43	0.50	0.67	24.0
ICON_010/90-29	29	TM12	20	0.14	0.19	3.3	3.5	5.6	0.46	0.74	0.99	19.4
ICON_010/90-43	43	TM13	20	0.22	0.29	3.4	4.4	7.0	0.41	0.68	0.91	32.4
ICON_010/90-58	58	TM14	20	0.34	0.46	2.9	3.5	10.2	0.46	0.65	0.87	53.1
ICON_010/90-86	86	TM15	20	0.44	0.59	3.6	5.0	14.8	0.55	0.96	1.29	45.8
ICON_010/90-173	173	TM16	20	0.88	1.18	4.8	8.1	25.2	0.67	1.56	2.09	56.4
ICON_020/180-22	22	TM13	40	0.22	0.29	3.4	4.4	7.0	0.41	0.68	0.91	32.4
ICON_020/180-29	29	TM14	40	0.34	0.46	2.9	3.5	10.2	0.46	0.65	0.87	53.1
ICON_020/180-43	43	TM15	40	0.44	0.59	3.6	5.0	14.8	0.55	0.96	1.29	45.8
ICON_020/180-58	58	TM21	20	0.63	0.85	4.8	8.1	15.7	0.43	1.00	1.34	63.0
ICON_020/180-86	86	TM22	20	0.95	1.27	5.3	10.4	23.3	0.61	1.57	2.10	60.5
ICON_020/180-173	173	TM23	20	1.75	2.35	8.7	14.3	47.2	0.67	2.83	3.79	62.0
ICON_030/360-29	29	TM21	40	0.63	0.85	4.8	8.1	15.7	0.43	1.00	1.34	63.0
ICON_030/360-58	58	TM30	20	1.36	1.82	10.3	17.3	36.3	0.43	2.15	2.88	63.1
ICON_030/360-86	86	TM23	40	1.75	2.35	8.7	14.3	47.2	0.67	2.83	3.79	62.0
ICON_030/360-173	173	TM31	20	4.05	5.43	14.6	30.1	101.1	0.68	4.81	6.45	84.2
ICON_040/720-29	29	TM30	40	1.36	1.82	10.3	17.3	36.3	0.43	2.15	2.88	63.1
ICON_040/720-43	43	TM40	40	2.02	2.71	10.3	20.5	56.7	0.67	3.35	4.48	60.5
ICON_040/720-86	86	TM31	40	4.05	5.43	14.6	30.1	101.1	0.68	4.81	6.45	84.2

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 29. 3-PH 400 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	TM00	40	0.04	0.05	0.5	0.6	0.8	0.46	0.16	0.21	24.0
ICON_010/30-22	22	TM01	40	0.05	0.07	0.5	0.7	1.1	0.42	0.15	0.19	36.7
ICON_010/30-29	29	TM10	20	0.09	0.12	1.7	2.0	3.4	0.43	0.51	0.68	17.4
ICON_010/30-43	43	TM03	20	0.09	0.12	0.9	1.08	1.68	0.46	0.46	0.29	31.0
ICON_010/30-58	58	TM04	20	0.17	0.23	1.5	2.8	3.9	0.47	0.49	0.65	34.7
ICON_010/30-86	86	TM05	20	0.26	0.34	1.4	3.1	6.1	0.56	0.54	0.73	47.2
ICON_010/30-173	173	TM06	20	0.51	0.69	2.0	2.9	8.4	0.71	0.98	1.32	52.1
ICON_010/90-14	14	TM10	40	0.09	0.12	1.7	2.0	3.4	0.43	0.51	0.68	17.4
ICON_010/90-22	22	TM11	40	0.13	0.18	1.7	1.9	3.9	0.43	0.51	0.68	26.1
ICON_010/90-29	29	TM12	20	0.15	0.19	2.2	2.5	3.9	0.46	0.70	0.94	20.7
ICON_010/90-43	43	TM13	20	0.23	0.30	2.4	3.1	4.9	0.41	0.68	0.91	33.3
ICON_010/90-58	58	TM14	20	0.35	0.46	2.0	2.5	7.1	0.46	0.64	0.85	54.4
ICON_010/90-86	86	TM15	20	0.45	0.60	2.5	3.5	10.4	0.55	0.95	1.28	46.9
ICON_010/90-173	173	TM16	20	0.89	1.19	3.3	5.6	17.6	0.67	1.53	2.05	58.0
ICON_020/180-22	22	TM13	40	0.23	0.30	2.4	3.1	4.9	0.41	0.68	0.91	33.3
ICON_020/180-29	29	TM14	40	0.35	0.46	2.0	2.5	7.1	0.46	0.64	0.85	54.4
ICON_020/180-43	43	TM15	40	0.45	0.60	2.5	3.5	10.4	0.55	0.95	1.28	46.9
ICON_020/180-58	58	TM21	20	0.63	0.85	3.3	5.6	11.0	0.43	0.98	1.32	64.4
ICON_020/180-86	86	TM22	20	0.96	1.29	3.7	7.3	16.3	0.61	1.56	2.10	61.4
ICON_020/180-173	173	TM23	20	1.77	2.37	6.0	10.0	33.1	0.67	2.79	3.73	63.5
ICON_030/360-29	29	TM21	40	0.63	0.85	3.3	5.6	11.0	0.43	0.98	1.32	64.4
ICON_030/360-58	58	TM30	20	1.36	1.82	7.1	12.1	25.4	0.43	2.12	2.83	64.1
ICON_030/360-86	86	TM23	40	1.77	2.37	6.0	10.0	33.1	0.67	2.79	3.73	63.5
ICON_030/360-173	173	TM31	20	4.04	5.42	10.0	21.1	70.8	0.68	4.71	6.31	85.8
ICON_040/720-29	29	TM30	40	1.36	1.82	7.1	12.1	25.4	0.43	2.12	2.83	64.1
ICON_040/720-43	43	TM40	40	2.04	2.73	7.1	14.4	39.7	0.67	3.30	4.42	61.8
ICON_040/720-86	86	TM31	40	4.04	5.42	10.0	21.1	70.8	0.68	4.71	6.31	85.8

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 30. 3-PH 440 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	TM00	40	0.04	0.06	0.5	0.5	0.6	0.46	0.18	0.23	24.0
ICON_010/30-22	22	TM01	40	0.06	0.08	0.5	0.6	0.8	0.42	0.16	0.21	36.7
ICON_010/30-29	29	TM10	20	0.09	0.11	1.5	1.7	2.6	0.43	0.49	0.66	17.4
ICON_010/30-43	43	TM03	20	0.09	0.12	0.82	0.94	1.47	0.46	0.46	0.29	31.0
ICON_010/30-58	58	TM04	20	0.17	0.23	1.4	2.5	3.0	0.47	0.50	0.67	34.7
ICON_010/30-86	86	TM05	20	0.26	0.35	1.3	2.7	4.7	0.56	0.55	0.74	47.2
ICON_010/30-173	173	TM06	20	0.51	0.68	1.8	2.6	6.4	0.71	0.97	1.31	52.1
ICON_010/90-14	14	TM10	40	0.09	0.11	1.5	1.7	2.6	0.43	0.49	0.66	17.4
ICON_010/90-22	22	TM11	40	0.13	0.17	1.5	1.6	3.0	0.43	0.49	0.66	26.1
ICON_010/90-29	29	TM12	20	0.15	0.19	2.0	2.2	3.0	0.46	0.70	0.94	20.7
ICON_010/90-43	43	TM13	20	0.22	0.29	2.1	2.7	3.8	0.41	0.66	0.88	33.3
ICON_010/90-58	58	TM14	20	0.34	0.46	1.8	2.2	5.5	0.46	0.63	0.85	54.4
ICON_010/90-86	86	TM15	20	0.45	0.61	2.3	3.1	7.9	0.55	0.96	1.29	46.9
ICON_010/90-173	173	TM16	20	0.89	1.19	3.0	4.9	13.5	0.67	1.53	2.05	58.0
ICON_020/180-22	22	TM13	40	0.22	0.29	2.1	2.7	3.8	0.41	0.66	0.88	33.3
ICON_020/180-29	29	TM14	40	0.34	0.46	1.8	2.2	5.5	0.46	0.63	0.85	54.4
ICON_020/180-43	43	TM15	40	0.45	0.61	2.3	3.1	7.9	0.55	0.96	1.29	46.9
ICON_020/180-58	58	TM21	20	0.63	0.85	3.0	4.9	8.4	0.43	0.98	1.32	64.4
ICON_020/180-86	86	TM22	20	0.95	1.27	3.3	6.4	12.5	0.61	1.53	2.06	61.8
ICON_020/180-173	173	TM23	20	1.78	2.39	5.5	8.7	25.3	0.67	2.81	3.76	63.5
ICON_030/360-29	29	TM21	40	0.63	0.85	3.0	4.9	8.4	0.43	0.98	1.32	64.4
ICON_030/360-58	58	TM30	20	1.34	1.80	6.4	10.5	19.4	0.43	2.10	2.81	64.1
ICON_030/360-86	86	TM23	40	1.78	2.39	5.5	8.7	25.3	0.67	2.81	3.76	63.5
ICON_030/360-173	173	TM31	20	4.05	5.42	9.1	18.3	54.1	0.68	4.72	6.32	85.8
ICON_040/720-29	29	TM30	40	1.34	1.80	6.4	10.5	19.4	0.43	2.10	2.81	64.1
ICON_040/720-43	43	TM40	40	2.02	2.71	6.4	12.5	30.3	0.67	3.27	4.38	61.8
ICON_040/720-86	86	TM31	40	4.05	5.42	9.1	18.3	54.1	0.68	4.72	6.32	85.8

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 31. 3-PH 460 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	TM00	40	0.04	0.05	0.4	0.5	0.7	0.46	0.15	0.20	24.0
ICON_010/30-22	22	TM01	40	0.06	0.08	0.5	0.6	0.9	0.42	0.17	0.22	36.7
ICON_010/30-29	29	TM10	20	0.08	0.11	1.4	1.7	2.7	0.43	0.48	0.64	17.4
ICON_010/30-43	43	TM03	20	0.09	0.12	0.78	0.92	1.46	0.46	0.46	0.29	31.0
ICON_010/30-58	58	TM04	20	0.17	0.23	1.3	2.4	3.1	0.47	0.49	0.65	34.7
ICON_010/30-86	86	TM05	20	0.25	0.34	1.2	2.6	4.9	0.56	0.54	0.72	47.2
ICON_010/30-173	173	TM06	20	0.50	0.67	1.7	2.5	6.7	0.71	0.96	1.29	52.1
ICON_010/90-14	14	TM10	40	0.08	0.11	1.4	1.7	2.7	0.43	0.48	0.64	17.4
ICON_010/90-22	22	TM11	40	0.13	0.17	1.4	1.6	3.1	0.43	0.48	0.64	26.1
ICON_010/90-29	29	TM12	20	0.14	0.19	1.9	2.1	3.1	0.46	0.70	0.93	20.7
ICON_010/90-43	43	TM13	20	0.23	0.30	2.1	2.6	3.9	0.41	0.69	0.92	32.8
ICON_010/90-58	58	TM14	20	0.34	0.45	1.7	2.1	5.7	0.46	0.62	0.83	54.4
ICON_010/90-86	86	TM15	20	0.45	0.61	2.2	3.0	8.3	0.55	0.96	1.29	46.9
ICON_010/90-173	173	TM16	20	0.90	1.20	2.9	4.8	14.1	0.67	1.55	2.07	58.0
ICON_020/180-22	22	TM13	40	0.23	0.30	2.1	2.6	3.9	0.41	0.69	0.92	32.8
ICON_020/180-29	29	TM14	40	0.34	0.45	1.7	2.1	5.7	0.46	0.62	0.83	54.4
ICON_020/180-43	43	TM15	40	0.45	0.61	2.2	3.0	8.3	0.55	0.96	1.29	46.9
ICON_020/180-58	58	TM21	20	0.64	0.86	2.9	4.8	8.8	0.43	0.99	1.33	64.4
ICON_020/180-86	86	TM22	20	0.95	1.28	3.2	6.2	13.0	0.61	1.56	2.08	61.4
ICON_020/180-173	173	TM23	20	1.76	2.36	5.2	8.5	26.4	0.67	2.78	3.72	63.5
ICON_030/360-29	29	TM21	40	0.64	0.86	2.9	4.8	8.8	0.43	0.99	1.33	64.4
ICON_030/360-58	58	TM30	20	1.34	1.80	6.1	10.3	20.3	0.43	2.09	2.80	64.1
ICON_030/360-86	86	TM23	40	1.76	2.36	5.2	8.5	26.4	0.67	2.78	3.72	63.5
ICON_030/360-173	173	TM31	20	4.05	5.43	8.7	17.9	56.5	0.68	4.71	6.32	86.0
ICON_040/720-29	29	TM30	40	1.34	1.80	6.1	10.3	20.3	0.43	2.09	2.80	64.1
ICON_040/720-43	43	TM40	40	2.01	2.70	6.1	12.2	31.7	0.67	3.26	4.36	61.8
ICON_040/720-86	86	TM31	40	4.05	5.43	8.7	17.9	56.5	0.68	4.71	6.32	86.0

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 32. 3-PH 480 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010/30-14	14	TM00	40	0.04	0.05	0.4	0.5	0.7	0.46	0.15	0.20	24.0
ICON_010/30-22	22	TM01	40	0.05	0.07	0.4	0.5	0.9	0.42	0.14	0.19	36.7
ICON_010/30-29	29	TM10	20	0.09	0.12	1.4	1.7	2.8	0.43	0.50	0.67	17.4
ICON_010/30-43	43	TM03	20	0.09	0.12	0.75	0.9	1.4	0.46	0.29	0.39	31.0
ICON_010/30-58	58	TM04	20	0.18	0.24	1.3	2.4	3.2	0.47	0.51	0.68	34.7
ICON_010/30-86	86	TM05	20	0.26	0.35	1.2	2.6	5.1	0.56	0.56	0.75	47.2
ICON_010/30-173	173	TM06	20	0.52	0.70	1.7	2.5	7.0	0.71	1.00	1.34	52.1
ICON_010/90-14	14	TM10	40	0.09	0.12	1.4	1.7	2.8	0.43	0.50	0.67	17.4
ICON_010/90-22	22	TM11	40	0.13	0.18	1.4	1.6	3.2	0.43	0.50	0.67	26.1
ICON_010/90-29	29	TM12	20	0.15	0.20	1.9	2.1	3.2	0.46	0.73	0.97	20.7
ICON_010/90-43	43	TM13	20	0.23	0.30	2.0	2.6	4.1	0.41	0.68	0.91	33.3
ICON_010/90-58	58	TM14	20	0.35	0.47	1.7	2.1	5.9	0.46	0.65	0.87	54.4
ICON_010/90-86	86	TM15	20	0.45	0.60	2.1	2.9	8.6	0.55	0.96	1.29	46.9
ICON_010/90-173	173	TM16	20	0.87	1.17	2.7	4.7	14.7	0.67	1.50	2.02	58.0
ICON_020/180-22	22	TM13	40	0.23	0.30	2.0	2.6	4.1	0.41	0.68	0.91	33.3
ICON_020/180-29	29	TM14	40	0.35	0.47	1.7	2.1	5.9	0.46	0.65	0.87	54.4
ICON_020/180-43	43	TM15	40	0.45	0.60	2.1	2.9	8.6	0.55	0.96	1.29	46.9
ICON_020/180-58	58	TM21	20	0.62	0.83	2.7	4.7	9.2	0.43	0.97	1.29	64.4
ICON_020/180-86	86	TM22	20	0.93	1.25	3.0	6.1	13.6	0.61	1.52	2.04	61.4
ICON_020/180-173	173	TM23	20	1.77	2.37	5.0	8.3	27.5	0.67	2.79	3.73	63.5
ICON_030/360-29	29	TM21	40	0.62	0.83	2.7	4.7	9.2	0.43	0.97	1.29	64.4
ICON_030/360-58	58	TM30	20	1.35	1.81	5.9	10.1	21.2	0.43	2.11	2.83	64.1
ICON_030/360-86	86	TM23	40	1.77	2.37	5.0	8.3	27.5	0.67	2.79	3.73	63.5
ICON_030/360-173	173	TM31	20	4.04	5.41	8.3	17.5	59.0	0.68	4.69	6.29	86.0
ICON_040/720-29	29	TM30	40	1.35	1.81	5.9	10.1	21.2	0.43	2.11	2.83	64.1
ICON_040/720-43	43	TM40	40	2.03	2.72	5.9	12.0	33.1	0.67	3.29	4.40	61.8
ICON_040/720-86	86	TM31	40	4.04	5.41	8.3	17.5	59.0	0.68	4.69	6.29	86.0

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

**Table 33. Modulating Duty (S4-50% 1200 St/h)
3-PH 220 V 50 Hz**

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-12	12	TM00	40	0.03	0.04	0.8	0.9	1.1	0.46	0.14	0.19	23.1
ICON_010R/30-18	18	TM01	40	0.05	0.07	0.8	1.0	1.4	0.42	0.13	0.17	38.3
ICON_010R/30-24	24	TM10	20	0.07	0.10	2.6	3.0	4.3	0.43	0.43	0.57	17.3
ICON_010R/30-36	36	TM03	20	0.07	0.10	1.36	1.6	2.33	0.46	0.24	0.32	31.0
ICON_010R/30-48	48	TM04	20	0.15	0.19	2.4	4.3	5.0	0.47	0.43	0.58	33.8
ICON_010R/30-72	72	TM05	20	0.22	0.29	2.2	4.6	7.8	0.56	0.47	0.63	46.3
ICON_010R/90-12	12	TM10	40	0.07	0.10	2.6	3.0	4.3	0.43	0.43	0.57	17.3
ICON_010R/90-18	18	TM11	40	0.11	0.15	2.6	2.9	5.0	0.43	0.43	0.57	25.9
ICON_010R/90-24	24	TM12	20	0.12	0.16	3.5	3.7	5.0	0.46	0.61	0.82	20.0
ICON_010R/90-36	36	TM13	20	0.18	0.24	3.6	4.6	6.3	0.41	0.56	0.75	32.1
ICON_010R/90-48	48	TM14	20	0.28	0.38	3.1	3.7	9.2	0.46	0.54	0.73	51.9
ICON_010R/90-72	72	TM15	20	0.36	0.48	3.8	5.3	13.3	0.55	0.80	1.07	45.0
ICON_020R/180-18	18	TM13	40	0.18	0.24	3.6	4.6	6.3	0.41	0.56	0.75	32.1
ICON_020R/180-24	24	TM14	40	0.28	0.38	3.1	3.7	9.2	0.46	0.54	0.73	51.9
ICON_020R/180-36	36	TM15	40	0.36	0.48	3.8	5.3	13.3	0.55	0.80	1.07	45.0
ICON_020R/180-48	48	TM21	20	0.52	0.70	5.1	8.5	14.1	0.43	0.84	1.12	62.7
ICON_020R/180-72	72	TM22	20	0.77	1.04	5.6	11.0	21.0	0.61	1.30	1.74	59.5
ICON_030R/360-24	24	TM21	40	0.52	0.70	5.1	8.5	14.1	0.43	0.84	1.12	62.7
ICON_030R/360-48	48	TM30	20	1.12	1.51	10.9	18.3	32.6	0.43	1.79	2.39	62.9
ICON_040R/720-24	24	TM30	40	1.12	1.51	10.9	18.3	32.6	0.43	1.79	2.39	62.9

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 34. 3-PH 230 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-12	12	TM00	40	0.03	0.04	0.7	0.8	1.1	0.46	0.13	0.17	22.4
ICON_010R/30-18	18	TM01	40	0.05	0.06	0.8	1.0	1.5	0.42	0.13	0.18	35.9
ICON_010R/30-24	24	TM10	20	0.07	0.09	2.4	3.0	4.5	0.43	0.41	0.55	17.0
ICON_010R/30-36	36	TM03	20	0.07	0.10	1.3	1.56	2.44	0.46	0.24	0.32	31.0
ICON_010R/30-48	48	TM04	20	0.14	0.19	2.3	4.2	5.2	0.47	0.43	0.58	33.5
ICON_010R/30-72	72	TM05	20	0.21	0.29	2.1	4.5	8.2	0.56	0.47	0.63	45.8
ICON_010R/90-12	12	TM10	40	0.07	0.09	2.4	3.0	4.5	0.43	0.41	0.55	17.0
ICON_010R/90-18	18	TM11	40	0.10	0.14	2.4	2.8	5.2	0.43	0.41	0.55	25.4
ICON_010R/90-24	24	TM12	20	0.12	0.16	3.3	3.7	5.2	0.46	0.60	0.81	20.2
ICON_010R/90-36	36	TM13	20	0.19	0.25	3.5	4.5	6.6	0.41	0.57	0.77	32.4
ICON_010R/90-48	48	TM14	20	0.29	0.39	3.0	3.7	9.6	0.46	0.55	0.74	52.8
ICON_010R/90-72	72	TM15	20	0.37	0.50	3.7	5.2	13.9	0.55	0.81	1.09	45.9
ICON_020R/180-18	18	TM13	40	0.19	0.25	3.5	4.5	6.6	0.41	0.57	0.77	32.4
ICON_020R/180-24	24	TM14	40	0.29	0.39	3.0	3.7	9.6	0.46	0.55	0.74	52.8
ICON_020R/180-36	36	TM15	40	0.37	0.50	3.7	5.2	13.9	0.55	0.81	1.09	45.9
ICON_020R/180-48	48	TM21	20	0.53	0.71	4.9	8.4	14.8	0.43	0.84	1.12	63.1
ICON_020R/180-72	72	TM22	20	0.79	1.06	5.4	10.8	21.9	0.61	1.31	1.76	60.2
ICON_030R/360-24	24	TM21	40	0.53	0.71	4.9	8.4	14.8	0.43	0.84	1.12	63.1
ICON_030R/360-48	48	TM30	20	1.12	1.50	10.4	17.9	34.1	0.43	1.78	2.39	62.8
ICON_040R/720-24	24	TM30	40	1.12	1.50	10.4	17.9	34.1	0.43	1.78	2.39	62.8

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 35. 3-PH 240 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-12	12	TM00	40	0.03	0.04	0.7	0.8	1.2	0.46	0.13	0.18	23.1
ICON_010R/30-18	18	TM01	40	0.05	0.06	0.7	0.9	1.5	0.42	0.12	0.16	38.3
ICON_010R/30-24	24	TM10	20	0.07	0.10	2.3	2.9	4.7	0.43	0.41	0.55	17.3
ICON_010R/30-36	36	TM03	20	0.07	0.10	1.25	1.53	2.54	0.46	0.24	0.32	31.0
ICON_010R/30-48	48	TM04	20	0.15	0.19	2.2	4.1	5.4	0.47	0.43	0.58	33.8
ICON_010R/30-72	72	TM05	20	0.22	0.29	2.0	4.4	8.5	0.56	0.47	0.62	46.3
ICON_010R/90-12	12	TM10	40	0.07	0.10	2.3	2.9	4.7	0.43	0.41	0.55	17.3
ICON_010R/90-18	18	TM11	40	0.11	0.14	2.3	2.7	5.4	0.43	0.41	0.55	25.9
ICON_010R/90-24	24	TM12	20	0.12	0.16	3.2	3.6	5.4	0.46	0.61	0.82	20.0
ICON_010R/90-36	36	TM13	20	0.18	0.24	3.3	4.4	6.9	0.41	0.56	0.75	32.1
ICON_010R/90-48	48	TM14	20	0.28	0.37	2.8	3.6	10.0	0.46	0.54	0.72	51.9
ICON_010R/90-72	72	TM15	20	0.36	0.48	3.5	5.1	14.5	0.55	0.80	1.07	45.0
ICON_020R/180-18	18	TM13	40	0.18	0.24	3.3	4.4	6.9	0.41	0.56	0.75	32.1
ICON_020R/180-24	24	TM14	40	0.28	0.37	2.8	3.6	10.0	0.46	0.54	0.72	51.9
ICON_020R/180-36	36	TM15	40	0.36	0.48	3.5	5.1	14.5	0.55	0.80	1.07	45.0
ICON_020R/180-48	48	TM21	20	0.53	0.71	4.7	8.2	15.4	0.43	0.84	1.13	62.7
ICON_020R/180-72	72	TM22	20	0.78	1.05	5.2	10.6	22.9	0.61	1.32	1.77	59.5
ICON_030R/360-24	24	TM21	40	0.53	0.71	4.7	8.2	15.4	0.43	0.84	1.13	62.7
ICON_030R/360-48	48	TM30	20	1.12	1.51	10.0	17.5	35.6	0.43	1.79	2.40	62.9
ICON_040R/720-24	24	TM30	40	1.12	1.51	10.0	17.5	35.6	0.43	1.79	2.40	62.9

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 36. 3-PH 380 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-12	12	TM00	40	0.03	0.04	0.4	0.5	0.6	0.46	0.12	0.16	23.1
ICON_010R/30-18	18	TM01	40	0.05	0.07	0.5	0.6	0.8	0.42	0.14	0.19	38.3
ICON_010R/30-24	24	TM10	20	0.07	0.10	1.5	1.7	2.5	0.43	0.42	0.57	17.3
ICON_010R/30-36	36	TM03	20	0.07	0.10	0.79	0.92	1.48	0.46	0.24	0.32	31.0
ICON_010R/30-48	48	TM04	20	0.15	0.20	1.4	2.5	2.9	0.47	0.43	0.58	33.8
ICON_010R/30-72	72	TM05	20	0.22	0.30	1.3	2.7	4.5	0.56	0.48	0.64	46.3
ICON_010R/90-12	12	TM10	40	0.07	0.10	1.5	1.7	2.5	0.43	0.42	0.57	17.3
ICON_010R/90-18	18	TM11	40	0.11	0.15	1.5	1.6	2.9	0.43	0.42	0.57	25.9
ICON_010R/90-24	24	TM12	20	0.12	0.16	2.0	2.2	2.9	0.46	0.61	0.81	20.3
ICON_010R/90-36	36	TM13	20	0.18	0.24	2.1	2.7	3.6	0.41	0.57	0.76	32.1
ICON_010R/90-48	48	TM14	20	0.29	0.39	1.8	2.2	5.2	0.46	0.54	0.73	53.0
ICON_010R/90-72	72	TM15	20	0.37	0.49	2.2	3.1	7.6	0.55	0.80	1.07	45.9
ICON_020R/180-18	18	TM13	40	0.18	0.24	2.1	2.7	3.6	0.41	0.57	0.76	32.1
ICON_020R/180-24	24	TM14	40	0.29	0.39	1.8	2.2	5.2	0.46	0.54	0.73	53.0
ICON_020R/180-36	36	TM15	40	0.37	0.49	2.2	3.1	7.6	0.55	0.80	1.07	45.9
ICON_020R/180-48	48	TM21	20	0.54	0.72	3.0	4.9	8.1	0.43	0.85	1.14	63.4
ICON_020R/180-72	72	TM22	20	0.80	1.08	3.3	6.4	12.0	0.61	1.32	1.78	60.7
ICON_030R/360-24	24	TM21	40	0.54	0.72	3.0	4.9	8.1	0.43	0.85	1.14	63.4
ICON_030R/360-48	48	TM30	20	1.13	1.51	6.3	10.6	18.6	0.43	1.78	2.39	63.1
ICON_040R/720-24	24	TM30	40	1.13	1.51	6.3	10.6	18.6	0.43	1.78	2.39	63.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 37. 3-PH 400 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-12	12	TM00	40	0.03	0.04	0.4	0.5	0.7	0.46	0.13	0.17	23.1
ICON_010R/30-18	18	TM01	40	0.04	0.06	0.4	0.6	0.9	0.42	0.12	0.16	38.3
ICON_010R/30-24	24	TM10	20	0.07	0.10	1.4	1.7	2.6	0.43	0.42	0.56	17.3
ICON_010R/30-36	36	TM03	20	0.07	0.10	0.75	0.9	1.4	0.46	0.24	0.32	31.0
ICON_010R/30-48	48	TM04	20	0.14	0.19	1.3	2.4	3.0	0.47	0.42	0.57	33.8
ICON_010R/30-72	72	TM05	20	0.22	0.29	1.2	2.6	4.7	0.56	0.47	0.62	46.3
ICON_010R/90-12	12	TM10	40	0.07	0.10	1.4	1.7	2.6	0.43	0.42	0.56	17.3
ICON_010R/90-18	18	TM11	40	0.11	0.14	1.4	1.6	3.0	0.43	0.42	0.56	25.9
ICON_010R/90-24	24	TM12	20	0.12	0.16	1.9	2.1	3.0	0.46	0.61	0.81	20.3
ICON_010R/90-36	36	TM13	20	0.19	0.25	2.0	2.6	3.8	0.41	0.57	0.76	32.9
ICON_010R/90-48	48	TM14	20	0.29	0.38	1.7	2.1	5.5	0.46	0.54	0.73	53.0
ICON_010R/90-72	72	TM15	20	0.37	0.49	2.1	3.0	8.0	0.55	0.80	1.07	45.9
ICON_020R/180-18	18	TM13	40	0.19	0.25	2.0	2.6	3.8	0.41	0.57	0.76	32.9
ICON_020R/180-24	24	TM14	40	0.29	0.38	1.7	2.1	5.5	0.46	0.54	0.73	53.0
ICON_020R/180-36	36	TM15	40	0.37	0.49	2.1	3.0	8.0	0.55	0.80	1.07	45.9
ICON_020R/180-48	48	TM21	20	0.53	0.71	2.8	4.8	8.5	0.43	0.83	1.12	63.4
ICON_020R/180-72	72	TM22	20	0.79	1.06	3.1	6.2	12.6	0.61	1.31	1.76	60.2
ICON_030R/360-24	24	TM21	40	0.53	0.71	2.8	4.8	8.5	0.43	0.83	1.12	63.4
ICON_030R/360-48	48	TM30	20	1.13	1.51	6.0	10.3	19.6	0.43	1.79	2.40	63.1
ICON_040R/720-24	24	TM30	40	1.13	1.51	6.0	10.3	19.6	0.43	1.79	2.40	63.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 38. 3-PH 415 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-12	12	TM00	40	0.03	0.04	0.4	0.5	0.7	0.46	0.13	0.18	23.1
ICON_010R/30-18	18	TM01	40	0.05	0.06	0.4	0.5	0.9	0.42	0.12	0.16	38.3
ICON_010R/30-24	24	TM10	20	0.07	0.10	1.4	1.7	2.7	0.43	0.43	0.58	17.3
ICON_010R/30-36	36	TM03	20	0.07	0.10	0.72	0.89	1.38	0.46	0.24	0.32	31.0
ICON_010R/30-48	48	TM04	20	0.15	0.20	1.3	2.4	3.1	0.47	0.44	0.59	33.8
ICON_010R/30-72	72	TM05	20	0.22	0.30	1.2	2.6	4.9	0.56	0.48	0.65	46.3
ICON_010R/90-12	12	TM10	40	0.07	0.10	1.4	1.7	2.7	0.43	0.43	0.58	17.3
ICON_010R/90-18	18	TM11	40	0.11	0.15	1.4	1.6	3.1	0.43	0.43	0.58	25.9
ICON_010R/90-24	24	TM12	20	0.12	0.16	1.8	2.1	3.1	0.46	0.60	0.80	20.3
ICON_010R/90-36	36	TM13	20	0.18	0.25	1.9	2.6	3.9	0.41	0.56	0.75	32.9
ICON_010R/90-48	48	TM14	20	0.28	0.38	1.6	2.1	5.7	0.46	0.53	0.71	53.0
ICON_010R/90-72	72	TM15	20	0.37	0.49	2.0	3.0	8.3	0.55	0.79	1.06	46.5
ICON_020R/180-18	18	TM13	40	0.18	0.25	1.9	2.6	3.9	0.41	0.56	0.75	32.9
ICON_020R/180-24	24	TM14	40	0.28	0.38	1.6	2.1	5.7	0.46	0.53	0.71	53.0
ICON_020R/180-36	36	TM15	40	0.37	0.49	2.0	3.0	8.3	0.55	0.79	1.06	46.5
ICON_020R/180-48	48	TM21	20	0.53	0.71	2.7	4.7	8.8	0.43	0.83	1.12	63.4
ICON_020R/180-72	72	TM22	20	0.79	1.06	3.0	6.1	13.1	0.61	1.32	1.76	60.2
ICON_030R/360-24	24	TM21	40	0.53	0.71	2.7	4.7	8.8	0.43	0.83	1.12	63.4
ICON_030R/360-48	48	TM30	20	1.13	1.52	5.8	10.1	20.3	0.43	1.79	2.40	63.1
ICON_040R/720-24	24	TM30	40	1.13	1.52	5.8	10.1	20.3	0.43	1.79	2.40	63.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 39. 3-PH 440 V 50 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-12	12	TM00	40	0.03	0.04	0.4	0.5	0.7	0.46	0.14	0.19	21.4
ICON_010R/30-18	18	TM01	40	0.05	0.06	0.4	0.5	0.9	0.42	0.13	0.17	35.4
ICON_010R/30-24	24	TM10	20	0.07	0.10	1.4	1.7	2.7	0.43	0.46	0.61	16.1
ICON_010R/30-36	36	TM03	20	0.07	0.10	0.75	0.9	1.4	0.46	0.24	0.32	31.0
ICON_010R/30-48	48	TM04	20	0.15	0.20	1.3	2.4	3.1	0.47	0.47	0.62	32.3
ICON_010R/30-72	72	TM05	20	0.22	0.30	1.2	2.6	4.9	0.56	0.51	0.69	43.5
ICON_010R/90-12	12	TM10	40	0.07	0.10	1.4	1.7	2.7	0.43	0.46	0.61	16.1
ICON_010R/90-18	18	TM11	40	0.11	0.15	1.4	1.6	3.1	0.43	0.46	0.61	24.1
ICON_010R/90-24	24	TM12	20	0.12	0.16	1.8	2.1	3.1	0.46	0.63	0.85	19.1
ICON_010R/90-36	36	TM13	20	0.18	0.24	1.9	2.6	3.9	0.41	0.59	0.80	30.7
ICON_010R/90-48	48	TM14	20	0.28	0.38	1.6	2.1	5.7	0.46	0.56	0.75	50.2
ICON_010R/90-72	72	TM15	20	0.37	0.49	2.0	3.0	8.3	0.55	0.84	1.12	43.7
ICON_020R/180-18	18	TM13	40	0.18	0.24	1.9	2.6	3.9	0.41	0.59	0.80	30.7
ICON_020R/180-24	24	TM14	40	0.28	0.38	1.6	2.1	5.7	0.46	0.56	0.75	50.2
ICON_020R/180-36	36	TM15	40	0.37	0.49	2.0	3.0	8.3	0.55	0.84	1.12	43.7
ICON_020R/180-48	48	TM21	20	0.53	0.71	2.7	4.7	8.8	0.43	0.88	1.19	59.8
ICON_020R/180-72	72	TM22	20	0.79	1.06	3.0	6.1	13.1	0.61	1.39	1.87	56.8
ICON_030R/360-24	24	TM21	40	0.53	0.71	2.7	4.7	8.8	0.43	0.88	1.19	59.8
ICON_030R/360-48	48	TM30	20	1.13	1.51	5.8	10.1	20.3	0.43	1.90	2.55	59.4
ICON_040R/720-24	24	TM30	40	1.13	1.51	5.8	10.1	20.3	0.43	1.90	2.55	59.4

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 40. 3-PH 280 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-14	14	TM00	40	0.04	0.05	0.7	0.8	1.2	0.46	0.16	0.21	22.5
ICON_010R/30-22	22	TM01	40	0.06	0.08	0.8	0.9	1.6	0.42	0.16	0.22	36.7
ICON_010R/30-29	29	TM10	20	0.08	0.11	2.4	2.9	4.8	0.43	0.50	0.67	16.0
ICON_010R/30-43	43	TM03	20	0.09	0.12	1.29	1.54	2.4	0.46	0.46	0.29	31.0
ICON_010R/30-58	58	TM04	20	0.17	0.23	2.2	4.0	5.6	0.47	0.50	0.67	34.0
ICON_010R/30-86	86	TM05	20	0.27	0.36	2.1	4.4	8.7	0.56	0.57	0.76	46.6
ICON_010R/90-14	14	TM10	40	0.08	0.11	2.4	2.9	4.8	0.43	0.50	0.67	16.0
ICON_010R/90-22	22	TM11	40	0.12	0.16	2.4	2.7	5.6	0.43	0.50	0.67	24.0
ICON_010R/90-29	29	TM12	20	0.14	0.19	3.3	3.5	5.6	0.46	0.74	0.99	19.4
ICON_010R/90-43	43	TM13	20	0.22	0.29	3.4	4.4	7.0	0.41	0.68	0.91	32.4
ICON_010R/90-58	58	TM14	20	0.34	0.46	2.9	3.5	10.2	0.46	0.65	0.87	53.1
ICON_010R/90-86	86	TM15	20	0.44	0.59	3.6	5.0	14.8	0.55	0.96	1.29	45.8
ICON_020R/180-22	22	TM13	40	0.22	0.29	3.4	4.4	7.0	0.41	0.68	0.91	32.4
ICON_020R/180-29	29	TM14	40	0.34	0.46	2.9	3.5	10.2	0.46	0.65	0.87	53.1
ICON_020R/180-43	43	TM15	40	0.44	0.59	3.6	5.0	14.8	0.55	0.96	1.29	45.8
ICON_020R/180-58	58	TM21	20	0.63	0.85	4.8	8.1	15.7	0.43	1.00	1.34	63.0
ICON_020R/180-86	86	TM22	20	0.95	1.27	5.3	10.4	23.3	0.61	1.57	2.10	60.5
ICON_030R/360-29	29	TM21	40	0.63	0.85	4.8	8.1	15.7	0.43	1.00	1.34	63.0
ICON_030R/360-58	58	TM30	20	1.36	1.82	10.3	17.3	36.3	0.43	2.15	2.88	63.1
ICON_040R/720-29	29	TM30	40	1.36	1.82	10.3	17.3	36.3	0.43	2.15	2.88	63.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 41. 3-PH 400 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-14	14	TM00	40	0.04	0.05	0.5	0.6	0.8	0.46	0.16	0.21	24.0
ICON_010R/30-22	22	TM01	40	0.05	0.07	0.5	0.7	1.1	0.42	0.15	0.19	36.7
ICON_010R/30-29	29	TM10	20	0.09	0.12	1.7	2.0	3.4	0.43	0.51	0.68	17.4
ICON_010R/30-43	43	TM03	20	0.09	0.12	0.9	1.08	1.68	0.46	0.46	0.29	31.0
ICON_010R/30-58	58	TM04	20	0.17	0.23	1.5	2.8	3.9	0.47	0.49	0.65	34.7
ICON_010R/30-86	86	TM05	20	0.26	0.34	1.4	3.1	6.1	0.56	0.54	0.73	47.2
ICON_010R/90-14	14	TM10	40	0.09	0.12	1.7	2.0	3.4	0.43	0.51	0.68	17.4
ICON_010R/90-22	22	TM11	40	0.13	0.18	1.7	1.9	3.9	0.43	0.51	0.68	26.1
ICON_010R/90-29	29	TM12	20	0.15	0.19	2.2	2.5	3.9	0.46	0.70	0.94	20.7
ICON_010R/90-43	43	TM13	20	0.23	0.30	2.4	3.1	4.9	0.41	0.68	0.91	33.3
ICON_010R/90-58	58	TM14	20	0.35	0.46	2.0	2.5	7.1	0.46	0.64	0.85	54.4
ICON_010R/90-86	86	TM15	20	0.45	0.60	2.5	3.5	10.4	0.55	0.95	1.28	46.9
ICON_020R/180-22	22	TM13	40	0.23	0.30	2.4	3.1	4.9	0.41	0.68	0.91	33.3
ICON_020R/180-29	29	TM14	40	0.35	0.46	2.0	2.5	7.1	0.46	0.64	0.85	54.4
ICON_020R/180-43	43	TM15	40	0.45	0.60	2.5	3.5	10.4	0.55	0.95	1.28	46.9
ICON_020R/180-58	58	TM21	20	0.63	0.85	3.3	5.6	11.0	0.43	0.98	1.32	64.4
ICON_020R/180-86	86	TM22	20	0.96	1.29	3.7	7.3	16.3	0.61	1.56	2.10	61.4
ICON_030R/360-29	29	TM21	40	0.63	0.85	3.3	5.6	11.0	0.43	0.98	1.32	64.4
ICON_030R/360-58	58	TM30	20	1.36	1.82	7.1	12.1	25.4	0.43	2.12	2.83	64.1
ICON_040R/720-29	29	TM30	40	1.36	1.82	7.1	12.1	25.4	0.43	2.12	2.83	64.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 42. 3-PH 440 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-14	14	TM00	40	0.04	0.06	0.5	0.5	0.6	0.46	0.18	0.23	24.0
ICON_010R/30-22	22	TM01	40	0.06	0.08	0.5	0.6	0.8	0.42	0.16	0.21	36.7
ICON_010R/30-29	29	TM10	20	0.09	0.11	1.5	1.7	2.6	0.43	0.49	0.66	17.4
ICON_010R/30-43	43	TM03	20	0.09	0.12	0.82	0.94	1.47	0.46	0.46	0.29	31.0
ICON_010R/30-58	58	TM04	20	0.17	0.23	1.4	2.5	3.0	0.47	0.50	0.67	34.7
ICON_010R/30-86	86	TM05	20	0.26	0.35	1.3	2.7	4.7	0.56	0.55	0.74	47.2
ICON_010R/90-14	14	TM10	40	0.09	0.11	1.5	1.7	2.6	0.43	0.49	0.66	17.4
ICON_010R/90-22	22	TM11	40	0.13	0.17	1.5	1.6	3.0	0.43	0.49	0.66	26.1
ICON_010R/90-29	29	TM12	20	0.15	0.19	2.0	2.2	3.0	0.46	0.70	0.94	20.7
ICON_010R/90-43	43	TM13	20	0.22	0.29	2.1	2.7	3.8	0.41	0.66	0.88	33.3
ICON_010R/90-58	58	TM14	20	0.34	0.46	1.8	2.2	5.5	0.46	0.63	0.85	54.4
ICON_010R/90-86	86	TM15	20	0.45	0.61	2.3	3.1	7.9	0.55	0.96	1.29	46.9
ICON_020R/180-22	22	TM13	40	0.22	0.29	2.1	2.7	3.8	0.41	0.66	0.88	33.3
ICON_020R/180-29	29	TM14	40	0.34	0.46	1.8	2.2	5.5	0.46	0.63	0.85	54.4
ICON_020R/180-43	43	TM15	40	0.45	0.61	2.3	3.1	7.9	0.55	0.96	1.29	46.9
ICON_020R/180-58	58	TM21	20	0.63	0.85	3.0	4.9	8.4	0.43	0.98	1.32	64.4
ICON_020R/180-86	86	TM22	20	0.95	1.27	3.3	6.4	12.5	0.61	1.53	2.06	61.8
ICON_030R/360-29	29	TM21	40	0.63	0.85	3.0	4.9	8.4	0.43	0.98	1.32	64.4
ICON_030R/360-58	58	TM30	20	1.34	1.80	6.4	10.5	19.4	0.43	2.10	2.81	64.1
ICON_040R/720-29	29	TM30	40	1.34	1.80	6.4	10.5	19.4	0.43	2.10	2.81	64.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 43. 3-PH 460 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-14	14	TM00	40	0.04	0.05	0.4	0.5	0.7	0.46	0.15	0.20	24.0
ICON_010R/30-22	22	TM01	40	0.06	0.08	0.5	0.6	0.9	0.42	0.17	0.22	36.7
ICON_010R/30-29	29	TM10	20	0.08	0.11	1.4	1.7	2.7	0.43	0.48	0.64	17.4
ICON_010R/30-43	43	TM03	20	0.09	0.12	0.78	0.92	1.46	0.46	0.46	0.29	31.0
ICON_010R/30-58	58	TM04	20	0.17	0.23	1.3	2.4	3.1	0.47	0.49	0.65	34.7
ICON_010R/30-86	86	TM05	20	0.25	0.34	1.2	2.6	4.9	0.56	0.54	0.72	47.2
ICON_010R/90-14	14	TM10	40	0.08	0.11	1.4	1.7	2.7	0.43	0.48	0.64	17.4
ICON_010R/90-22	22	TM11	40	0.13	0.17	1.4	1.6	3.1	0.43	0.48	0.64	26.1
ICON_010R/90-29	29	TM12	20	0.14	0.19	1.9	2.1	3.1	0.46	0.70	0.93	20.7
ICON_010R/90-43	43	TM13	20	0.23	0.30	2.1	2.6	3.9	0.41	0.69	0.92	32.8
ICON_010R/90-58	58	TM14	20	0.34	0.45	1.7	2.1	5.7	0.46	0.62	0.83	54.4
ICON_010R/90-86	86	TM15	20	0.45	0.61	2.2	3.0	8.3	0.55	0.96	1.29	46.9
ICON_020R/180-22	22	TM13	40	0.23	0.30	2.1	2.6	3.9	0.41	0.69	0.92	32.8
ICON_020R/180-29	29	TM14	40	0.34	0.45	1.7	2.1	5.7	0.46	0.62	0.83	54.4
ICON_020R/180-43	43	TM15	40	0.45	0.61	2.2	3.0	8.3	0.55	0.96	1.29	46.9
ICON_020R/180-58	58	TM21	20	0.64	0.86	2.9	4.8	8.8	0.43	0.99	1.33	64.4
ICON_020R/180-86	86	TM22	20	0.95	1.28	3.2	6.2	13.0	0.61	1.56	2.08	61.4
ICON_030R/360-29	29	TM21	40	0.64	0.86	2.9	4.8	8.8	0.43	0.99	1.33	64.4
ICON_030R/360-58	58	TM30	20	1.34	1.80	6.1	10.3	20.3	0.43	2.09	2.80	64.1
ICON_040R/720-29	29	TM30	40	1.34	1.80	6.1	10.3	20.3	0.43	2.09	2.80	64.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Table 44. 3-PH 480 V 60 Hz

Size, Torque, Speed	RPM	Motor	INT WG Ratio (:1)	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-14	14	TM00	40	0.04	0.05	0.4	0.5	0.7	0.46	0.15	0.20	24.0
ICON_010R/30-22	22	TM01	40	0.05	0.07	0.4	0.5	0.9	0.42	0.14	0.19	36.7
ICON_010R/30-29	29	TM10	20	0.09	0.12	1.4	1.7	2.8	0.43	0.50	0.67	17.4
ICON_010R/30-43	43	TM03	20	0.09	0.12	0.75	0.9	1.4	0.46	0.46	0.29	31.0
ICON_010R/30-58	58	TM04	20	0.18	0.24	1.3	2.4	3.2	0.47	0.51	0.68	34.7
ICON_010R/30-86	86	TM05	20	0.26	0.35	1.2	2.6	5.1	0.56	0.56	0.75	47.2
ICON_010R/90-14	14	TM10	40	0.09	0.12	1.4	1.7	2.8	0.43	0.50	0.67	17.4
ICON_010R/90-22	22	TM11	40	0.13	0.18	1.4	1.6	3.2	0.43	0.50	0.67	26.1
ICON_010R/90-29	29	TM12	20	0.15	0.20	1.9	2.1	3.2	0.46	0.73	0.97	20.7
ICON_010R/90-43	43	TM13	20	0.23	0.30	2.0	2.6	4.1	0.41	0.68	0.91	33.3
ICON_010R/90-58	58	TM14	20	0.35	0.47	1.7	2.1	5.9	0.46	0.65	0.87	54.4
ICON_010R/90-86	86	TM15	20	0.45	0.60	2.1	2.9	8.6	0.55	0.96	1.29	46.9
ICON_020R/180-22	22	TM13	40	0.23	0.30	2.0	2.6	4.1	0.41	0.68	0.91	33.3
ICON_020R/180-29	29	TM14	40	0.35	0.47	1.7	2.1	5.9	0.46	0.65	0.87	54.4
ICON_020R/180-43	43	TM15	40	0.45	0.60	2.1	2.9	8.6	0.55	0.96	1.29	46.9
ICON_020R/180-58	58	TM21	20	0.62	0.83	2.7	4.7	9.2	0.43	0.97	1.29	64.4
ICON_020R/180-86	86	TM22	20	0.93	1.25	3.0	6.1	13.6	0.61	1.52	2.04	61.4
ICON_030R/360-29	29	TM21	40	0.62	0.83	2.7	4.7	9.2	0.43	0.97	1.29	64.4
ICON_030R/360-58	58	TM30	20	1.35	1.81	5.9	10.1	21.2	0.43	2.11	2.83	64.1
ICON_040R/720-29	29	TM30	40	1.35	1.81	5.9	10.1	21.2	0.43	2.11	2.83	64.1

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.

Single-Phase AC

Table 45. Short-Time Duty (S2-15') | Inching Duty (S4-25% | 60 St/h)
1-PH 110 V 50 Hz

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-SR1	TM11	40	8	17	0.11	0.15	2.3	3.1	6.8	0.53	0.13	0.18	81.5
ICON_010R/30-SR2	TM14	20	18	62	0.28	0.38	5.1	6.7	10.7	0.58	0.33	0.44	87.5
ICON_010R/30-SR3	TM15	20	63	94	0.37	0.50	5.6	8.4	16.5	0.69	0.43	0.57	87.4
ICON_010R/90-SR1	TM13	40	6	23	0.19	0.25	4.8	6.3	12.1	0.58	0.31	0.41	61.3
ICON_010R/90-SR2	TM14	20	24	40	0.28	0.38	6.1	9.1	17.8	0.69	0.46	0.62	60.9
ICON_020R/180-SR1	TM21	40	8	20	0.53	0.71	10.3	15.5	26.0	0.54	0.61	0.82	86.2

Table 46. 1-PH 115 V 50 Hz

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-SR1	TM11	40	8	17	0.11	0.15	2.2	3.0	7.1	0.53	0.13	0.18	81.5
ICON_010R/30-SR2	TM14	20	18	62	0.29	0.38	4.9	6.4	11.2	0.58	0.33	0.44	87.5
ICON_010R/30-SR3	TM15	20	63	94	0.37	0.50	5.4	8.1	17.3	0.69	0.43	0.57	87.4
ICON_010R/90-SR1	TM13	40	6	23	0.19	0.25	4.6	6.0	12.7	0.58	0.31	0.41	61.3
ICON_010R/90-SR2	TM14	20	24	40	0.28	0.38	5.8	8.7	18.6	0.69	0.46	0.62	60.9
ICON_020R/180-SR1	TM21	40	8	20	0.53	0.71	9.9	14.8	27.1	0.54	0.61	0.82	86.2

Table 47. 1-PH 220 V 50 Hz

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-SR1	TM11	40	8	17	0.11	0.15	1.2	1.6	3.7	0.53	0.14	0.19	81.5
ICON_010R/30-SR2	TM15	20	24	72	0.37	0.50	2.6	4.5	9.2	0.69	0.39	0.53	94.1
ICON_010R/30-SR3	TM16	20	73	172	0.17	0.23	2.4	4.1	8.7	0.85	0.45	0.60	38.5
ICON_010R/90-SR1	TM13	40	6	23	0.18	0.25	4.6	6.0	10.6	0.55	0.56	0.75	32.9
ICON_010R/90-SR2	TM18	20	24	95	0.50	0.67	5.8	8.7	18.6	0.8	1.02	1.37	49.0
ICON_020R/180-SR1	TM22	40	12	36	0.79	1.06	5.5	10.0	16.7	0.85	1.03	1.38	76.6
ICON_020R/180-SR2	TM22	20	48	60	0.79	1.06	7.8	15.6	29.1	0.85	1.46	1.95	54.0
ICON_030R/360-SR1	TM30	40	10	30	1.13	1.51	12.4	21.3	29.5	0.57	1.55	2.08	72.5

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.
- Data referred to maximum allowable actuator speed.

Table 48. 1-PH 230 V 50 Hz

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-SR1	TM11	40	8	17	0.11	0.15	1.1	1.5	3.9	0.53	0.13	0.18	81.5
ICON_010R/30-SR2	TM15	20	24	72	0.37	0.50	2.5	4.3	9.6	0.69	0.40	0.53	94.1
ICON_010R/30-SR3	TM16	20	73	172	0.17	0.23	2.3	3.9	9.1	0.85	0.45	0.60	38.5
ICON_010R/90-SR1	TM13	40	6	23	0.18	0.25	4.4	5.8	11.1	0.55	0.56	0.75	32.9
ICON_010R/90-SR2	TM18	20	24	95	0.50	0.68	5.6	8.3	19.4	0.8	1.03	1.38	49.0
ICON_020R/180-SR1	TM22	40	12	36	0.79	1.06	5.3	9.5	17.5	0.85	1.04	1.39	76.6
ICON_020R/180-SR2	TM22	20	48	60	0.79	1.06	7.5	15.0	30.4	0.85	1.47	1.96	54.0
ICON_030R/360-SR1	TM30	40	10	30	1.12	1.50	11.8	20.3	30.8	0.57	1.55	2.07	72.5

Table 49. 1-PH 120 V 60 Hz

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-SR1	TM11	40	8	17	0.13	0.17	2.1	2.9	7.4	0.53	0.13	0.18	97.7
ICON_010R/30-SR2	TM14	20	18	62	0.29	0.38	4.7	6.1	11.7	0.58	0.33	0.44	87.5
ICON_010R/30-SR3	TM15	20	63	94	0.37	0.49	5.1	7.7	18.0	0.69	0.42	0.57	87.4
ICON_010R/90-SR1	TM13	40	6	23	0.22	0.30	5.5	10.7	23.0	0.41	0.27	0.36	81.9
ICON_010R/90-SR2	TM14	20	24	40	0.34	0.46	6.4	10.5	22.7	0.72	0.55	0.74	61.8
ICON_020R/180-SR1	TM21	40	8	20	0.21	0.29	9.4	14.2	28.3	0.54	0.61	0.82	35.2

Table 50. 1-PH 240 V 60 Hz

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-SR1	TM11	40	8	17	0.14	0.18	1.1	1.4	4.0	0.53	0.14	0.19	97.7
ICON_010R/30-SR2	TM15	20	24	72	0.37	0.50	2.4	4.1	10.0	0.69	0.40	0.53	94.1
ICON_010R/30-SR3	TM16	20	73	172	0.17	0.23	2.2	3.7	9.5	0.85	0.45	0.60	38.5
ICON_010R/90-SR1	TM13	40	6	23	0.22	0.29	4.2	5.5	11.6	0.55	0.55	0.74	39.5
ICON_010R/90-SR2	TM18	20	24	95	0.50	0.67	5.3	8.0	20.3	0.8	1.02	1.36	49.0
ICON_020R/180-SR1	TM22	40	12	36	0.96	1.28	5.1	9.1	18.3	0.85	1.04	1.39	91.9
ICON_020R/180-SR2	TM22	20	48	60	0.95	1.28	7.2	14.3	31.7	0.85	1.47	1.97	64.9
ICON_030R/360-SR1	TM30	40	10	30	1.36	1.82	11.4	19.5	32.1	0.57	1.56	2.09	87.0

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.
- Data referred to maximum allowable actuator speed.

Table 51. Modulating Duty (S4-50% - 1200 St/h)
1-PH 110 V 50 Hz

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-SR1	TM11	40	8	17	0.11	0.15	2.3	3.1	6.8	0.53	0.13	0.18	81.5
ICON_010R/30-SR2	TM14	20	18	62	0.28	0.38	5.1	6.7	10.7	0.58	0.33	0.44	87.5
ICON_010R/30-SR3	TM15	20	63	94	0.37	0.50	5.6	8.4	16.5	0.69	0.43	0.57	87.4
ICON_010R/90-SR1	TM13	40	6	23	0.19	0.25	4.8	6.3	12.1	0.58	0.31	0.41	61.3
ICON_010R/90-SR2	TM14	20	24	40	0.28	0.38	6.1	9.1	17.8	0.69	0.46	0.62	60.9
ICON_020R/180-SR1	TM21	40	8	20	0.53	0.71	10.3	15.5	26.0	0.54	0.61	0.82	86.2

Table 52. 1-PH 115 V 50 Hz

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-SR1	TM11	40	8	17	0.11	0.15	2.2	3.0	7.1	0.53	0.13	0.18	81.5
ICON_010R/30-SR2	TM14	20	18	62	0.29	0.38	4.9	6.4	11.2	0.58	0.33	0.44	87.5
ICON_010R/30-SR3	TM15	20	63	94	0.37	0.50	5.4	8.1	17.3	0.69	0.43	0.57	87.4
ICON_010R/90-SR1	TM13	40	6	23	0.19	0.25	4.6	6.0	12.7	0.58	0.31	0.41	61.3
ICON_010R/90-SR2	TM14	20	24	40	0.28	0.38	5.8	8.7	18.6	0.69	0.46	0.62	60.9
ICON_020R/180-SR1	TM21	40	8	20	0.53	0.71	9.9	14.8	27.1	0.54	0.61	0.82	86.2

Table 53. 1-PH 220 V 50 Hz

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-SR1	TM11	40	8	17	0.11	0.15	1.2	1.6	3.7	0.53	0.14	0.19	81.5
ICON_010R/30-SR2	TM15	20	24	72	0.37	0.50	2.6	4.5	9.2	0.69	0.39	0.53	94.1
ICON_010R/30-SR3	TM16	20	73	172	0.17	0.23	2.4	4.1	8.7	0.85	0.45	0.60	38.5
ICON_010R/90-SR1	TM13	40	6	23	0.18	0.25	4.6	6.0	10.6	0.55	0.56	0.75	32.9
ICON_010R/90-SR2	TM18	20	24	95	0.50	0.67	5.8	8.7	18.6	0.8	1.02	1.37	49.0
ICON_020R/180-SR1	TM22	40	12	36	0.79	1.06	5.5	10.0	16.7	0.85	1.03	1.38	76.6
ICON_020R/180-SR2	TM22	20	48	60	0.79	1.06	7.8	15.6	29.1	0.85	1.46	1.95	54.0
ICON_030R/360-SR1	TM30	40	10	30	1.13	1.51	12.4	21.3	29.5	0.57	1.55	2.08	72.5

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.
- Data referred to maximum allowable actuator speed.

Table 54. 1-PH 230 V 50 Hz

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-SR1	TM11	40	8	17	0.11	0.15	1.1	1.5	3.9	0.53	0.13	0.18	81.5
ICON_010R/30-SR2	TM15	20	24	72	0.37	0.50	2.5	4.3	9.6	0.69	0.40	0.53	94.1
ICON_010R/30-SR3	TM16	20	73	172	0.17	0.23	2.3	3.9	9.1	0.85	0.45	0.60	38.5
ICON_010R/90-SR1	TM13	40	6	23	0.18	0.25	4.4	5.8	11.1	0.55	0.56	0.75	32.9
ICON_010R/90-SR2	TM18	20	24	95	0.50	0.68	5.6	8.3	19.4	0.8	1.03	1.38	49.0
ICON_020R/180-SR1	TM22	40	12	36	0.79	1.06	5.3	9.5	17.5	0.85	1.04	1.39	76.6
ICON_020R/180-SR2	TM22	20	48	60	0.79	1.06	7.5	15.0	30.4	0.85	1.47	1.96	54.0
ICON_030R/360-SR1	TM30	40	10	30	1.12	1.50	11.8	20.3	30.8	0.57	1.55	2.07	72.5

Table 55. 1-PH 120 V 60 Hz

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-SR1	TM11	40	8	17	0.13	0.17	2.1	2.9	7.4	0.53	0.13	0.18	97.7
ICON_010R/30-SR2	TM14	20	18	62	0.29	0.38	4.7	6.1	11.7	0.58	0.33	0.44	87.5
ICON_010R/30-SR3	TM15	20	63	94	0.37	0.49	5.1	7.7	18.0	0.69	0.42	0.57	87.4
ICON_010R/90-SR1	TM13	40	6	23	0.22	0.30	5.5	10.7	23.0	0.41	0.27	0.36	81.9
ICON_010R/90-SR2	TM14	20	24	40	0.34	0.46	6.4	10.5	22.7	0.72	0.55	0.74	61.8
ICON_020R/180-SR1	TM21	40	8	20	0.21	0.29	9.4	14.2	28.3	0.54	0.61	0.82	35.2

Table 56. 1-PH 240 V 60 Hz

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010R/30-SR1	TM11	40	8	17	0.14	0.18	1.1	1.4	4.0	0.53	0.14	0.19	97.7
ICON_010R/30-SR2	TM15	20	24	72	0.37	0.50	2.4	4.1	10.0	0.69	0.40	0.53	94.1
ICON_010R/30-SR3	TM16	20	73	172	0.17	0.23	2.2	3.7	9.5	0.85	0.45	0.60	38.5
ICON_010R/90-SR1	TM13	40	6	23	0.22	0.29	4.2	5.5	11.6	0.55	0.55	0.74	39.5
ICON_010R/90-SR2	TM18	20	24	95	0.50	0.67	5.3	8.0	20.3	0.8	1.02	1.36	49.0
ICON_020R/180-SR1	TM22	40	12	36	0.96	1.28	5.1	9.1	18.3	0.85	1.04	1.39	91.9
ICON_020R/180-SR2	TM22	20	48	60	0.95	1.28	7.2	14.3	31.7	0.85	1.47	1.97	64.9
ICON_030R/360-SR1	TM30	40	10	30	1.36	1.82	11.4	19.5	32.1	0.57	1.56	2.09	87.0

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.
- Data referred to maximum allowable actuator speed.

Direct Current

Table 57. Inching duty (S4-25%, 600 St/h)
24 V DC

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010D/30-SR1	DM05d	40	12	29	0.15	0.20	14.0	28.0	65.0	0	0.34	0.45	43.9
ICON_010D/30-SR2	DM05d	20	30	60	0.15	0.20	14.0	28.0	65.0	0	0.34	0.45	43.9
ICON_010D/90-SR1	DM05	40	12	23	0.19	0.26	14.0	32.0	63.0	0	0.34	0.45	57.6
ICON_010D/90-SR2	DM05	20	24	30	0.20	0.27	20.0	38.0	55.0	0	0.34	0.45	57.6
ICON_010D/90-SR3	DM05	20	50	68	0.19	0.26	37.0	80.0	120.0	0	0.89	1.19	21.6

Table 58. 48 V DC

Size, Torque, Speed	Motor	INT WG Ratio (:1)	RPM Min	RPM Max	Power (KW)	Power (HP)	In (A)	Is (A)	Icc (A)	Power Factor	Absorbed Power (KW)	Absorbed Power (HP)	Efficiency (%)
ICON_010D/30-SR1	DM05d	40	12	29	0.15	0.20	7.0	14.0	33.0	0	0.34	0.45	43.9
ICON_010D/30-SR2	DM05d	20	30	60	0.15	0.20	7.0	14.0	33.0	0	0.34	0.45	43.9
ICON_010D/90-SR1	DM05	20	50	68	0.40	0.54	16.5	32.0	58.0	0	0.79	1.06	50.6
ICON_010D/90-SR1	DM05	40	12	30	0.40	0.54	16.5	32.0	58.0	0	0.79	1.06	50.6
ICON_010D/90-SR2	DM05	20	50	68	0.40	0.54	16.5	32.0	58.0	0	0.79	1.06	50.6

NOTES:

- Nominal Duty is in according to IEC 60034-1.
- Motor insulation: Class H.
- Due to manufacturing tolerances, there may be deviations from the published values.
- Data referred to maximum allowable actuator speed.

This page is intentionally left blank.

Biffi Italia s.r.l.
Strada Biffi 165
29017 Fiorenzuola d'Arda (PC)
Italy
T +39 0523 944 411

For complete list of sales and manufacturing sites, please visit
www.biffi.it or contact us at biffi_italia@biffi.it

FCDS-20149-EN © 2024 Biffi. All rights reserved.

The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available upon request. We reserve the right to modify or improve the designs or specifications of such products at any time without notice.

